


New Vanguard

OSPREY
PUBLISHING

Challenger Main Battle Tank 1982–97



Simon Dunstan • Illustrated by Peter Sarson


SIMON DUNSTAN is a well-established author, film maker and photographer in the field of military history, and has written several titles for Osprey. He specialises in the subject of armoured warfare, a field on which he has been writing for two decades. His books have covered topics such as helicopter and armoured warfare in Vietnam, the British Guards and armoured warfare in Korea. Simon lives and works in London.

PETER SARSON has produced graphic cutaways for many armoured vehicle publications, and is regarded as one of the world's great illustrators of military vehicles. Peter lives and works in Dorset.

New Vanguard • 23

OSPREY
PUBLISHING

Challenger Main Battle Tank 1982–97



Simon Dunstan • Illustrated by Peter Sarson

First published in Great Britain in 1998 by
Osprey Publishing, Elms Court, Chapel Way,
Botley, Oxford OX2 9LP, United Kingdom.
Email: info@ospreypublishing.com

© Copyright 1998 Osprey Publishing Ltd.
Reprinted 2002, 2003

All rights reserved. Apart from any fair dealing for the purpose of private study, research, criticism or review, as permitted under the Copyright, Designs and Patents Act, 1988, no part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, electrical, chemical, mechanical, optical, photocopying, recording or otherwise, without the prior permission of the copyright owner. Enquiries should be addressed to the Publishers.

CIP Data for this publication is available from the British Library

ISBN 1 85532 485 7

Military Editor: Iain MacGregor
Design: Alan Hamp

Series Editor: MARTIN WINDROW
Filmset in Great Britain
Printed in China through World Print Ltd.

FOR A CATALOGUE OF ALL BOOKS PUBLISHED BY
OSPREY MILITARY AND AVIATION PLEASE CONTACT:

The Marketing Manager, Osprey Direct UK,
PO Box 140, Wellingborough, Northants,
NN8 2FA, United Kingdom.
Email: info@ospreydirect.co.uk

The Marketing Manager, Osprey Direct USA,
c/o MBI Publishing, PO Box 1,
729 Prospect Avenue, Osceola, WI 54020, USA.
Email: info@ospreydirectusa.com

www.ospreypublishing.com

Acknowledgments

Lt Col Nigel Aylwin-Foster RTR, Major-General Patrick Cordingley DSO (retd), Col Charles Delamain (retd), David Fletcher, Christopher F. Foss, Angus Fraser (formerly Scots DG), Piers German (formerly LG), WO2 Ken Gifford QRL, Col John Gillman OBE, S/Sgt Kevin Greenhalgh RTR, HQ RAC Centre, Major Albert Hogg KRH, Major Mick Keats RH, Capt Simon Keymer RTR, Denis Lunn MBE, Sgt Colin McKerrell SCOTS DG, Major (retd) Toby Maddison MC, Lt Col Patrick Marriot QRL, Tim Neate, Capt Will Packard QRL, Public Information Land Command & British Forces Germany, David Rowlands, Cpl Colin Shaw KRH, WO1 Bob Soanes RTR, WO2 Tony Sterling QRL, Col T W Terry OBE, Col (Retd) Mike Vickery OBE, VDS, and Steve Zaloga.

Artist's Note

Readers may care to note the original paintings from which the colour plates in this book were prepared are available for private sale. All reproduction copyright whatsoever is retained by the Publishers. All enquiries should be addressed to:

Peter Sarson, 46 Robert-Louis Stevenson Avenue, Westbourne,
Bournemouth, Dorset BH4 8EJ

The Publishers regret that they can enter into no correspondence upon this matter.

CHALLENGER MAIN BATTLE TANK 1982-97

DESIGN AND DEVELOPMENT

Tank design is a continuous process and, even before a Main Battle Tank (MBT) enters service, concepts and characteristics for its successor are being explored. By 1970, Chieftain MBT was in widespread service with the British Army and, in the following year, the Imperial Iranian Army ordered 780 Chieftains. Designated Chieftain Mark 3/3(P) while the remainder were Mark 5(P) – the P standing for Persia, these models differed only in detail from those in the British Army and all were delivered by 1977. Further purchases of Chieftain were made by Kuwait and Oman giving Britain a strong tank manufacturing industry throughout the 1970s.

The Arab-Israeli War of 1967 had reaffirmed the importance of the tank on the battlefield and demonstrated that heavy armour in its design was a worthwhile attribute, despite the emergence of hollow or shaped charge infantry weapons and anti-tank guided missiles in ever increasing numbers. Indeed, some pundits were proclaiming the demise of the tank in the face of the alarming penetrative power of hollow charge weapons, known hereafter as HEAT (High Explosive Anti-Tank) which uses chemical energy to burn through armour. As a rule of thumb, contemporary HEAT warheads would penetrate steel armour to a depth four times their cone diameter. Such designs incorporated cones typically of

Three generations of British battle tanks thunder down a track at Bovington, the home of the Royal Armoured Corps during comparative testing by the Armoured Trials and Development Unit in 1982. The evolutionary nature of British tank designs since World War 2 is readily apparent in this photograph with, from left to right, Challenger, Chieftain and Centurion. (Mike Garrard - MOD)



the order of 84mm (3¼ inches) capable of penetrating up to 340mm (13 inches) of steel. Soviet weapons of this period were the shoulder-fired RPG-7 with a 73mm (3 inches) warhead and the man-portable, wire-guided Sagger AT-3 (Malyutka) anti-tank missile with a 150mm (6 inches) warhead

and a penetrative power of 600mm (24 inches). With 170 missile launchers and 600 RPG-7s in a typical Soviet motor rifle division, these posed a formidable threat to NATO tanks and any conventional design able to withstand such attack would weigh over 200 tonnes. At the same time, contemporary Soviet tanks such as the T-62 and T-64 had larger main armaments, at 115mm and 125mm respectively, than Western tanks which had standardised on the British L7 105mm gun, except for Chieftain with its 120mm. The Soviets had also pioneered the use of Armour Piercing Fin Stabilized Discarding Sabot (APFSDS) ammunition. This was a highly effective round for killing tanks at the ranges for armoured combat envisaged by Soviet planners.

Faced with such threats, Western designers investigated the properties of different forms of armour with the emphasis on trying to thwart attack from HEAT weapons. During the late '50s and early '60s various experiments had been conducted using steel alloy and ceramic laminates which had proved promising but these were difficult to manufacture and therefore expensive. In Britain Dr Gilbert Harvey, a scientist at the Royal Armament Research and Development Establishment (RARDE) at Chertsey, made an interesting discovery when investigating ways to protect fuel cells inside AFVs. By incorporating honeycomb structures composed of certain materials which were intended to inhibit the explosive nature of the fuel, the effectiveness of HEAT rounds was demonstrably diminished. Further experimentation followed and significant successes were achieved against HEAT attack. A programme ensued which would not only defeat HEAT weapons but be effective also against AP, APDS and HESH projectiles; High Explosive Squash Head



The Imperial Iranian Army was a major user of Chieftain and employed it extensively during the Iran/Iraq War, where it gained a reputation for being able to sustain extensive battle damage. This is a Chieftain Mark 5/3(P) or FV4030/1 which was similar to British Army models but for several improvements such as an automatic gearbox to simplify driver training. (MOD)

The second model in the FV4030 range or Shir Iran 1 (Lion of Persia) featured a revised suspension known as Super Horstmann and a lengthened hull to incorporate the new powerpack comprising the 1200 bhp Rolls Royce engine and David Brown gearbox. With the fall of the Shah of Iran, this model was purchased by the Royal Jordanian Army as Khalid. (MOD)



(HESH) being another type of chemical energy armour defeating round favoured by the British.

After a thorough process of testing and trials, the new composite armour, now known as Chobham, was incorporated in an experimental aluminium tank in 1971 designated FV4211 which was based on Chieftain components; Chobham being the name of the town closest to the Military Vehicles and Engineering Establishment (MVEE), formerly RARDE, where it was developed. The construction of the FV4211 coincided with the outset of the US XM-1 programme and, following Anglo-American agreements on the reciprocal exchange of research, details of Chobham armour were passed to the Americans. Trials in the United States demonstrated the remarkable protection afforded by Chobham armour and it was readily incorporated into the XM-1 prototypes being produced by Chrysler and General Motors.

Indeed, the M-1 Abrams was to be the first tank to be put into full production with Chobham armour because the development of FV4211 was terminated in 1972. This followed a decision taken by the governments of Britain and the Federal Republic of Germany (FRG) to develop a single design known as Future Main Battle Tank (FMBT) to replace Chieftain and Leopard 1 respectively. The concept of standardisation within NATO was much espoused at this time and there were perceived to be attractive economic benefits to be accrued from the sharing of development costs. However, as the abortive US/FRG MBT-70 programme had recently proved, joint tank programmes were fraught with difficulties and so it proved once more. As joint discussions ranged over a wide gamut of options another war erupted in the Middle East in October 1973 and once again the future of the tank was thrown into doubt.

Fighting on a scale unseen since World War 2, heavy casualties both in men and machines were suffered by attackers and defenders alike with many of the Israeli losses being attributed to the widespread use by Arab forces of Sagger anti-tank guided missiles and the profligate

The first tank to carry the revolutionary new protection that came to be known as Chobham armour was the FV4211. Using mainly Chieftain Mark 5 components, it was designed and built in the remarkably short time of ten months and two weeks (the designers had hoped to beat the fastest development cycle of a British tank hitherto; that being Churchill at ten months and one week). The FV4211 was a truly innovative design featuring a welded and fabricated hull and turret shell made of aluminium plate instead of the costly castings for the Chieftain. As these parts constituted only 8 per cent of the total vehicle cost, they were expendable and, during refit, all the other components, once refurbished, such as the powerplant, fire control system and Chobham armour envelope could be installed on another shell. However, such a radical concept was not pursued although its influence on the XM-1 programme was significant.(MOD)



A rare photograph shows one of the Concept Test Rigs devised and trialled during the Anglo-German FMBT (Future Main Battle Tank) programme of the 1970s. The design incorporated several standard Chieftain assemblies such as the Horstmann suspension and the L-60 powerplant although the engine compartment was configured to take either a British or a German powerpack. With Chobham armour protecting the frontal aspect, the semi-fixed 120mm main armament was aimed by slewing the vehicle through a hydraulic steering system; the gun only moving in elevation. Because of its configuration and the nature of the bilateral programme, the vehicle was known as Jagdchieftain. (Colonel John Gillman OBE)



deployment of RPG weapons among their infantry. In fact, less than a tenth of Israeli tanks destroyed in battle had been due to missiles and most of these occurred during the first Israeli counter-attacks against the Egyptian incursion across the Suez Canal when Israeli tank crews employed cavalier tactics without sufficient infantry support. However, this fact did not emerge until long after the war following lengthy analysis of Israeli tank losses. There was no doubt, however, that there had been some serious shortcomings in the Western tanks employed by the Israelis not least of which was their capacity to sustain battle damage and continue fighting; an attribute now termed 'survivability'.

During the October War, the Israeli Army was mainly equipped with American M-48 and M-60 tanks in the Sinai Desert against the Egyptians, while on the Golan Heights against the Syrians and Iraqis it used the British Centurion which had been extensively reworked to accommodate the Continental diesel engine of the M-60 with its dependable performance and reduced fire risks. All these tanks shared the same main armament in the well-proven British designed L7/M68 105mm gun. The nature of the fighting for the Israelis differed dramatically between the defensive battles conducted in the close terrain of the Golan to the offensive operations in the wide open desert of the Sinai with, at the outset of the war, a lack of customary air superiority.

Invidious comparisons have been drawn between the American and British designs but the M-60 did suffer some significant losses with high crew casualties due to two major factors. The first was the use of a hydraulic turret traverse which necessitated high pressure lines in the crew compartment. If these lines were ruptured when the tank was hit, a highly inflammable mist was sprayed around inside the tank causing terrible burns to the crews should it ignite. The second was the practice of stowing ammunition in the turret bustle. Since the majority of hits occurred in the turret, the ammunition was often penetrated resulting in catastrophic fires. These were lessons learned long ago by the British and the Centurion had an electric turret traverse, even though this meant a more cramped turret and slower traverse, and all combustible ammunition was stowed in the hull below the level of the turret; a practice followed by Chieftain.

For these reasons, British designers felt vindicated in their design philosophy. The Germans however were less happy since Leopard 1 shared an ammunition stowage layout and turret traverse system similar to the M-60 but with even less armour protection. A replacement was deemed a priority by the Bundeswehr and it accelerated the development of prototypes of a design that had been formulated following the demise of MBT-70; subsequently to emerge as Leopard 2. However the design study for FMBT continued in Britain and Germany with many interesting and innovative concepts, both conventional and unconventional, being addressed. Eventually the study established the requirement for a conventional four man tank with a turret but no agreement could be reached on the timescale for the

introduction of FMBT nor on the vexed question of work sharing, in particular the division of work to satisfy production orders for foreign customers such as the Iranians. The project was terminated by mutual agreement in 1977.

In the meantime, a further major order for Chieftain had been received from the Imperial Iranian Army (IIA) in December 1974. The contract provided for the supply of 1200 Chieftains of an improved version to be called Shir Iran (Lion of Persia); the Ministry of Defence gave the programme the series designation FV4030. In particular the IIA sought improvements in reliability and power output over the troublesome L-60 engine of Chieftain. The design of a new engine was undertaken by Rolls Royce in conjunction with David Brown Gear Industries for the automatic transmission, combined into a single powerpack assembly. Its proposed configuration however was too large for the existing Chieftain hull so a new vehicle had to be developed to accommodate it.

The design was based on that of FV4211 but with Chobham armour mounted on a steel turret and hull; an L11 120mm main armament with the Improved Fire Control System then being introduced into the British Army and a hydropneumatic suspension system produced by Dunlop. Pending the full development of these features, production continued of a basic Chieftain Mark 5 modified to meet the Iranian specifications with an automatic gearbox, increased mine protection and extra fuel capacity under the designation Mark 5/3(P) or FV4030/1. The first of a batch of 150 was completed in July 1976. Stage two of the FV4030 project was essentially a Chieftain Mark 5/3(P) with a revised rear hull to accommodate the new powerpack. The first three prototypes of FV4030/2 were completed by the beginning of 1977 and it was

The MBT-80 was a tank of conventional configuration with a fully-rotating turret and a four-man crew. The photograph depicts the only remaining example of the MBT-80 programme which is now at the Tank Museum at Bovington. It features an early research turret mounted on a test rig hull. Of particular note is the offset high pressure 120mm rifled gun to allow more room for the gunner and the sophisticated fire control system which was an early example of what is now termed the 'Hunter-Killer' type with panoramic sights and thermal imaging. In the event, MBT-80 was an over-ambitious project which ran seriously over budget and it was cancelled in 1979. (The Tank Museum)



demonstrated to the Iranians in March under the name Shir Iran 1.

Problems with the steering units of the TN-37 transmission delayed volume production of Shir Iran 1 as well as development trials of the full specification Shir Iran 2 or FV4030/3, prototypes of which were running during 1977. Production of Shir 1 (the name had now changed) got underway in 1978, with that of Shir 2 being scheduled to start in April 1979, but the fall of the Shah of Iran precipitated the cancellation of the complete contract in February 1979. Fortunately, the Royal Jordanian Army adopted the FV4030/2 as the Khalid MBT and placed an order for 274 in November of that year with deliveries beginning in 1981.

After the collapse of the Anglo-German FMBT project in 1977, Britain was obliged to seek a new solution to Chieftain's replacement. Consideration was given to the purchase of an MBT from another country; the two foreign contenders being the XM-1 and, ironically, Leopard 2. Both tanks were due to enter service in the next few years and the purchase of either would have much enhanced standardisation within NATO. However, as the in-service date requirement for Chieftain's successor was not until the late '80s, it was felt that both designs would be several years old by then and on this basis neither tank would have fully met the needs of the British Army. Similarly, consideration was given to the purchase of Shir 2, at that time at an advanced stage of design, as it was attractive for political and economic reasons as well as enjoying significant commonality with Chieftain to simplify training. Again, like Leopard 2 and XM-1, Shir 2 was being produced to an earlier technological standard and, despite its use of Chobham armour and other technical advances, it did not meet the longer term operational requirements, particularly in regards to its fire control system.

For these reasons, development began of a new tank project designated MBT-80. Drawing on the Anglo-German programme it was to be a tank of conventional turreted design carrying a four man crew. Concept studies addressed the three fundamental areas of MBT design - firepower, protection and mobility. The choice of a main armament proved to be a particularly difficult one between the German 120mm smooth bore gun or a further development of the well proven British 120mm rifled gun. The latter was chosen because of its perceived advantages of being able to fire a greater variety of ammunition natures. In particular it would be able to fire both fin-stabilised and spin-stabilised ammunition, thus allowing more flexibility in defeating the new types of armour arrays then being introduced as well as provide fire support to the infantry with the superior high explosive capability of the HESH round.



The final model of FV4030 developed for the Imperial Iranian Army was the Shir Iran 2, subsequently known as Shir 2, which was the first to feature the Hydrogas suspension system. One of the reasons for the demise of the FV4211 and the development of FV4030 was the insistence of the IIA on an all-steel tank, because of the problems of stress corrosion cracking associated with aluminium armour. (MOD)

The tank was to be built with Chobham armour but with increased protection against top and bottom attack. As to mobility, the stated requirement was a power-to-weight ratio of approximately 27bhp/t for a vehicle of 55 tonnes which predicated an engine of 1500hp. The choice of engine was narrowed to two options: a 1500hp version of the Rolls Royce CV12 TCA diesel and the Avco Lycoming AGT-1500 gas turbine as fitted in the XM-1 Abrams. There was an influential school of thought that favoured the gas turbine so no final decision had been made when the MBT-80 entered the project definition phase in September 1978 which was to last approximately two years. A decision concerning the powerplant was due in mid-1979 with the project entering full development by 1981. Development prototypes were to appear round about 1983-1984 with a design cut-off date in 1985 followed by definitive development models the following year. The in-service date of MBT-80 remained "in the late '80s".

Even by this timescale it was apparent that the British Army would not field an MBT with Chobham armour until almost 20 years after the appearance of FV4211. However, during 1979 it became evident that MBT-80 was unlikely to enter service until the 1990s and the escalating costs of development were proving considerable. With the Soviet Union producing increasingly capable tanks such as the T-64/72 at the rate of over 2000 a year, a new tank for the British Army became evermore urgent. Accordingly, in September 1979 it was decided to introduce a limited number of FV4030/3 models adapted to suit British Army requirements but without major modifications so as to speed development and production with minimal additional costs. As a result the MBT-80 programme was cancelled but a research programme continued to identify an eventual replacement for Chieftain.

The new tank was to be called Challenger¹ and an order was placed for 243, sufficient to equip four armoured regiments together with training and reserve vehicles. Between 1980 and 1981, seven prototype Challengers were built which underwent extensive trials at MVEE and with the Armoured Trials and Development Unit (ATDU) at Bovington. As part of the accelerated development programme, more than 100,000kms of automotive running were completed to assess the reliability, availability, maintainability and durability aspects, or RAM-D as it was then termed. Initial automotive user trials of two prototypes (V4C1 and V4C2) by ATDU were begun in January 1981 but were soon stopped because of recurring failures of the TN37 gearbox. After modifications, ATDU resumed automotive testing in November with an additional two prototypes (V4C5 and V4C6) in what became known as 'The 7-Pack Trial'.

Throughout 1982 development continued and the problems associated with the clutch design and the hydrostatic steering units were addressed by the two companies involved, David Brown Gear Industries and Commercial Hydraulics. Further automotive trials demonstrated that the hydrogas suspension provided excellent cross-country performance and high reliability. In October 1982 Exercise Challenger Trophy 2 was conducted by ATDU on Salisbury Plain involving four

¹ The decision to call the new MBT Challenger showed a lack of originality as this name had been previously used for the Heavy Cruiser Tank A30, an indifferent design that saw limited service in the final years of World War 2. Of interest, both tanks share the design limitation of a narrow internal mantlet for the main armament which is not conducive to consistent high accuracy.

prototypes on a four-day battlefield exercise. The tanks performed very well and, although Challenger's nominal top speed is 56kph, it regularly exceeded 70kph across the plain. Challenger was accepted for service with the British Army by the General Staff on 14 December 1982 with certain provisos, namely:-

Proven solutions had to be found for the problems associated with the following aspects of Challenger -

1. Main engine generator drive
2. Neodymium YAG Tank Laser Sight
3. Tools and Test Equipment
4. TN37 Gearbox
5. Fightability
6. No 79 Sight
7. Scale of major assembly spares

The first regiment to be issued with Challenger was The Royal Hussars which received their first one on 12 April 1983.



ABOVE The first production model Challenger was delivered to the British Army on 16 March 1983 during a ceremony at the Royal Ordnance Factory Leeds. Although this vehicle has the armoured barbette for TOGS on the turret side, TOGS was still under development so this is a Challenger Mark 1. Once TOGS was installed the tank became a Mark 2. (MOD)



CHALLENGER TECHNICAL DESCRIPTION


Driver's compartment

Challenger is a logical development of the Chieftain MBT with substantial advances in the areas of armour protection and mobility, the latter being the main deficiency of its predecessor. The layout of Challenger is conventional with the hull of welded construction being sub-divided with the driver's compartment at the front, the turret and fighting compartment placed centrally and the power train at the rear. Access to the driver's position is through a hatch in the glacis plate. The driver reclines when closed down and is provided with an armoured periscope situated behind the hatch. The driver's position is central with linked steering levers to each side. Brake and accelerator pedals are normal and a footrest is positioned under the left foot. The speedometer and main engine switchboard are to the driver's right. Mounted low on the right are the GUE (Generator Unit Engine) and emergency gear controls (both difficult to get to when closed down) and, to their rear, the gear selector which operates in a gate with six gear range positions plus neutral. Two hull batteries are located to the driver's left with

RIGHT The gunner's position in a Challenger 1 is to the right of the gun breach and forward of the tank commander - note the TOGS viewing screen in the centre of the photograph.

BOTTOM RIGHT A view of the commander's position shows the plethora of electronic boxes and gadgets that comprises the fire control and turret systems of Challenger. (QRL)

LEFT The first regiment to be equipped with Challenger was the Royal Hussars from April 1983. Challenger has a conventional layout with the driver located centrally in the hull front. The driver and commander are seated on the right hand side of the turret with the loader to the left of the breach. The British Army remains convinced of the efficacy of the four-man crew to sustain the 24-hour battle. (Soldier Magazine)



projectile racks above. A further two batteries and projectile racks are to his right with a stowage pannier above for the driver's personal equipment. By fully lowering his seat the driver can move rearwards into the fighting compartment.

Fighting compartment

The main armament of Challenger is the well proven L11A5 120mm rifled gun as used on Chieftain. The gun has a semi-automatically operating breech with a fume extractor mid-way along its length. It fires separated ammunition, the charge being contained in a fully combustible bag ignited by a 'Tube Vent Electric'. The projectiles and charges are loaded by hand. The charges are ignited by the electrically fired vent tubes; 14 of which are held in a magazine on the breech ring. Being a rifled gun, a wide range of ammunition can be fired including APDS-T (L15A4); APFSDS-T (L23A1); DS-T (L20A1); HESH (L31A7); HESH practice (L32A5); Smoke WP (L34A2) and Canister (L35A1).

The commander is seated at the right rear of the turret with the gunner forward and slightly below him. The commander has a No.32 cupola with fixed unity periscopes providing all round vision and a No.37 combined day/night sight giving the commander x10 and x1 unity vision by day and x4 vision by night. The cupola can be traversed independently of the turret and a 7.62mm L37A2 is mounted externally which can be cocked, elevated and fired from under armour.

The gunner's main sight is a periscopic Tank Laser Sight No.10 Mark 1 with a magnification of x1 and x10. The laser rangefinder is a Neodmium Yag with an operating range of 300 to 10,000 metres with the distance being displayed in both the gunner's and commander's sights. These are integral with the Computerised Sighting System (CSS). Designed by Marconi Command and Control Systems, the CSS integrates information

from the laser rangefinder with that of target movement and vehicle attitude from sensors built into the system and automatically calculates the appropriate lay of the main armament. The gun and turret are then driven to the correct position, the gun being stabilised in both axes. Since Challenger was designed primarily to fight from prepared positions covering designated arcs of fire CSS significantly increases the probability of a first round hit against moving targets, particularly at long ranges. The system also allows the gunner to keep targets under close observation while on the

The first major exercise conducted by The Royal Hussars as a complete regiment with Challenger was Exercise Lionheart near Hildesheim in West Germany in September 1984. It is apparent that this is a Challenger Mark 1 as the stowage of kit on the turret front would obscure the angle of view of the TISH if TOGS was installed. (MOD)



move and then make final adjustments for firing at the short halt, the preferred method of tank engagements in the British Army. The tank is also equipped with the Muzzle Reference System which allows the gunner to check any deviation in the gun barrel alignment with the sights and make adjustments without leaving his position in the tank.

One of the major innovations of Challenger was the introduction of TOGS - Thermal Observation and Gunnery System. The system enables Challenger to detect, track and engage targets with equal facility by day or night and, being completely passive, without betraying its own position. It is also highly effective in adverse weather and battlefield conditions, such as mist and smoke. The TOGS system has two principal elements - the Thermal Surveillance System (TSS) and the Gunnery Sighting System (GSS). The TSS comprises the actual thermal imaging equipment of TOGS which picks out any object that radiates heat against the difference in thermal characteristics of its background. Known as the TISH or Thermal Imager Sensor Head, it is mounted within a servo trunnion unit inside an armoured barbette on the exterior of the tank turret. With a dual field of view, the TISH provides a general surveillance and vehicle navigation facility in wide angle and allows target recognition and gun aiming in the narrow angle. The thermal radiation detected by TISH is converted into electrical signals suitable for presentation once they have passed through the Symbology Processing Unit or SPU (pronounced 'spew') which is the control centre of TOGS. This computer integrates data from multiple sources in the GSS and, in essence, turns what would otherwise be a thermal camera into a gunsight. Positioned adjacent to the gunner's and commander's stations, both Individual Visual Display Units show identical information with graticule, aiming marks and ballistic data generated on the thermal picture for gunnery by either crewman with the commander having an override facility.

Challenger is the first tank in British Army service to be fitted with Chobham armour which gives it excellent protection against HEAT warheads that make up the majority of anti-tank weapons on the battlefield. On Challenger the highest level of protection is provided on the hull and turret fronts, giving immunity against the largest hollow charge projectiles such as the Russian AT-4 Spigot which can penetrate 500mm (20 inches) of conventional steel armour. The armour configuration also gives high protection against kinetic energy rounds. According to US sources, the protection over the frontal arc of both Challenger and the M1A1 Abrams is equivalent to about 1000mm (40 inches) of steel armour. While no Challengers were hit by heavy calibre weapons in the Gulf War, seven M1A1s suffered direct frontal hits from tank guns, mainly from the 125mm main armament of T-72, but no penetrations or crew casualties ensued.

Undoubtedly the most dramatic difference between Challenger and Chieftain is the greatly enhanced mobility and agility despite an overall weight of 60 tonnes. Challenger has an integrated powerpack incorporating the engine, transmission and cooling group in a single assembly which can be removed and replaced in under an hour. The powerpack can also be run up on a trolley outside the vehicle for fault finding and tuning. An auxiliary power unit or GUE, provides electrical power for silent watch operation and to assist in main engine starting.

The main engine is a Perkins Engines (formerly Rolls Royce) Condor V12 TCA diesel engine with a rated power of 895 kw (1200 bhp) at 2300 rpm. Exhaust gas turbocharging and charge air cooling devised by Garret-AiResearch are employed to maximise power output from a capacity of 26.1 litres giving Challenger a power-to-weight ratio of approximately 20 bhp/tonne. The engine is located at the front centre of the powerpack compartment with the transmission bolted directly behind it.

The transmission is the David Brown Vehicle Transmission (formerly David Brown Gear Industries) TN37 epicyclic gearbox which allows gear changes to be made while the gearbox is transmitting power. Four forward and three reverse gears are provided with an automatic controller selecting the optimum gear ratio. Incorporated into the TN37 transmission is the Commercial Hydraulics STN37 steer unit giving a continuously variable output with hydrostatically transmitted power. This provides Challenger with an infinitely variable turning capability including a neutral turn whereby the vehicle revolves about its centre. Similarly, the main brakes which are of an oil immersed multi-plate type are incorporated in the TN37 transmission.

Much of the impressive improvement in the cross-country performance of Challenger is due to the hydrogas suspension system which provides progressive spring characteristics with highly efficient damping and large wheel deflection resulting in a much improved vehicle ride across all types of terrain. The total weight of the suspension system is 25 per cent less than the Horstmann bogie type of Chieftain and maintenance is considerably reduced. Being completely independent of each other, the individual wheel stations are simple to replace; so avoiding the vulnerability and complexity of coupled systems or those using torsion bars which are notoriously difficult to repair following mine damage.

Challenger variants

CRARRV - Challenger Armoured Repair and Recovery Vehicle

During the troop trial conducted by The Royal Hussars in 1983, the Chieftain ARRV proved incapable of supporting Challenger MBT adequately. In 1984, the Ministry of Defence invited tenders for the development and manufacture of an ARRV based on the running gear of Challenger. Competitive bids were submitted by Royal Ordnance Leeds and Vickers Defence Systems (VDS). The latter was awarded a fixed price contract in June 1985 for the production of 30 vehicles. By the use of newly acquired Computer Aided Design facilities and years of experience in the manufacture of Centurion and Chieftain ARVs, Vickers completed the first CRARRV in August 1987 and the remaining five of the pre-production models in December; a remarkably short development cycle by any standards.

After intensive trials lasting for 14 months, the production run of 26 CRARRVs began in 1989 with four of the pre-production models being subsequently refurbished to production standard to complete the initial contract for 30 vehicles. Several features on the pre-production models, such as the cradle to carry a spare CV12 powerpack over the engine decks, had to be sacrificed to meet the weight and height restrictions of bridges in Germany; a spare powerpack now being carried in a Warrior Trailer as required. The CRARRV was accepted for service with the British Army in June 1990 with a planned in-service date of May 1991 but

this schedule was to be overtaken by events following the invasion of Kuwait by the Iraqi Army in August 1990.

As its designation implies, the CRARRV can be used both for recovery and repair of MBTs in the field. The vehicle carries an extensive range of repair equipment, including welding and cutting equipment and air tools, as well as an Atlas AK6000 M8 hydraulic crane capable of lifting a complete Challenger powerpack. With its TN54 transmission giving much improved manoeuvrability at low speeds and excellent mobility to keep pace with Challenger formations, CRARRV has proved to be an outstanding vehicle from the outset of its service with the British Army. It is capable of towing AFVs of up to 70 tonnes in weight at speeds of up to 30 kph. A further advantage of CRARRV over other support vehicles is that it has been designed to enable a significant amount of repair to be undertaken on MBTs in the field. Such was its success in the Gulf War that a subsequent order for 50 additional CRARRVs was placed with Vickers Defence Systems, the last of which was delivered in early 1993.

CTT - Challenger Training Tank

In February 1988, the Ministry of Defence placed an order with Vickers Defence Systems for the supply of 17 Challenger Training Tanks. In a fixed price contract valued at £18m, these were the first purpose designed training tanks procured by the British Army. As approximately 60 per cent of the total cost of a modern MBT comprises the turret systems, particularly the fire control system, a specialised training vehicle makes economic sense and such a vehicle has been commonplace in European armies for many years. Delivery of the 17 CTTs was made during 1990 and they entered service in 1991. They are used for driver and maintenance training by both the Royal Armoured Corps and the Royal Electrical and Mechanical Engineers.

There have been several private venture weapons systems mounted on the Challenger hull such as the Marconi Marksman twin 35mm

A Challenger 1 Mark 2 Control Tank of Ajax Squadron, 2 RTR, moves down a track during an exercise in West Germany. The primary lens of the TISH is readily apparent with the TOGS door open. This Challenger is fitted with external fuel tanks at the rear, first trialed in 1987, to augment the tanks' range from their bases to the Inner German Border during times of crisis. (MOD)



anti-aircraft gun turret and the Royal Ordnance GBT 155mm howitzer turret. Future variants of Challenger for the British Army may include a Beach Armoured Recovery Vehicle (BARV) as well as a bridgelayer and combat engineer versions to replace Chieftain AVLB (Armoured Vehicle Launched Bridge) and Chieftain AVRE (Armoured Vehicle Royal Engineers) once Challenger 2 is in widespread service.


CANADIAN ARMY TROPHY 1987

By May 1985, The Royal Hussars were fully equipped with Challenger. Meanwhile, the second armoured regiment to be converted to the new MBT, 2 Royal Tank Regiment (2 RTR), received its first Challenger in late 1984. The next two armoured regiments scheduled to be converted were the 17th/21st Lancers (17/21L) and the Queen's Royal Irish Hussars (QRIH). In June 1984, the Ministry of Defence placed an order for an additional 64 Challengers which was sufficient to equip a fifth armoured regiment in BAOR.

Despite its recent introduction into service there were reservations in certain quarters about Challenger concerning that most important aspect of an MBT – its fire control system which was almost identical to that of Chieftain, itself based on early 1960s technology. Inevitably comparisons were drawn with other MBTs then in full scale service such as the M1 Abrams and Leopard 2. This was confirmed following the Canadian Army Trophy of 1985 or CAT '85. Open to all member nations of NATO in the Central Region, the competition was intended to improve the overall standard of tank gunnery within the alliance. However, over the years, it had assumed the character more of a gladiatorial contest with unhappy connotations of national superiority; notwithstanding the commercial kudos attached to the brand of MBT winning the competition.

Unfortunately for the British Army, The Royal Scots Dragoon Guards mounted in Chieftain came last in the CAT '85 competition. Widely regarded as one of the most proficient armoured regiments within the Royal Armoured Corps, the SCOTS DG were longstanding users of Chieftain and had come second in CAT '83. The result was all the more disappointing as they were firing on home territory at the Hohne Ranges. There were no doubts in the minds of the SCOTS DG where the problems lay and that improvements had to be made to the fire control

1:76 scale side view drawing of a
Rhino CRAARV. (Tim Neate)



system to improve engagement times as well as providing more extensive technical support for the competition. They also recommended that a regiment be selected as soon as possible for the next CAT and that the crews be drawn from across the regiment rather than a single squadron.

In fact, the latter had been addressed when, based on excellent gunnery results achieved in 1984, 2nd Royal Tank Regiment (2 RTR) was chosen to represent 1 (BR) Corps for CAT '87 in time to witness CAT '85. 2 RTR were thus able to lay careful plans that autumn and devise selection procedures to concentrate the necessary talent. Mindful of the implications another disappointing performance would have for the prestige of the British Army and its equipment, the then Chief of the General Staff directed that Challenger be fielded for the next competition. The inherent limitations of Challenger were acknowledged and the overall aim was one of damage limitation in the full knowledge that Challenger could not be expected to win but hopefully would finish among the weaker M1 and Leopard 2 platoons. Throughout 1986, 2 RTR geared gunnery training towards the objectives of CAT '87 and the annual firing in July was used to select competition crews from across the regiment. They were also able to influence timely decisions affecting equipment enhancements deemed necessary for CAT '87 including early procurement of the Improved Computerised Sighting System (ICSS); albeit in prototype form, which in preliminary trials had suggested that engagement times could be halved compared with IFCS.

Following CAT '85, the Committee of Control again tried to eliminate the gladiatorial aspects of the competition and the participating nations were asked to submit proposals to this end. After much discussion and horse trading, a revised set of rules was promulgated in January 1986; however the rules also decreed that each nation must select its entrant from one of two units decided by a random draw held ten weeks before the competition.

This produced a considerable problem for the British Army as its options for the second regiment were strictly limited. Of the 13 armoured regiments, six were equipped with Chieftain which ruled them out while two (17/21L and QRH) were converting to Challenger

The Challenger Armoured Repair and Recovery Vehicle is manned by members of the Royal Electrical and Mechanical Engineers. It is operated by a crew of three and can carry up to four additional crew or passengers. CRARRV is the first AFV to be developed and manufactured by a private contractor since World War 2. It is also the first to be produced as a fixed-price contract. (MOD)





Camouflaged in the characteristic yellow and green disruptive stripes of OPFOR (Opposing Forces) vehicles, a CRARRV prepares to tow a Chieftain of 1 RTR during Exercise Phantom Bugle on Salisbury Plain in June 1995. CRARRV has a multi-purpose blade which can operate as an earth anchor, dozer blade or stabiliser for the hydraulically-operated crane, with all controls under armour and is equipped with a hydraulically-driven double capstan winch and an independent auxiliary winch. (Tim Neate)

but neither had TOGS, which was considered vital for target acquisition at Grafenwohr with its heated target displays where CAT '87 was to be held. The only other contender was The Royal Hussars who had a squadron fitted with TOGS and had the further advantage of being co-located with 2 RTR. However, The Royal Hussars were committed in 1986 to BATUS in Canada which entailed converting back to Chieftain when they should be training on Challenger/TOGS for CAT.

Meanwhile, 22 Challenger MBTs with TOGS (36KA26-44) were specially prepared to provide each contending squadron with new tanks built to exacting quality assurance standards. These were diverted from the production line resulting in delays to those regiments converting to Challenger. They also incorporated several modifications fitted solely for CAT. Besides the ICSS, these included a finely tuned Tank Laser Sight; a Chase modified loader's firing guard²; a less cluttered graticule in the gunner's sight, a revised loading mechanism and an alternative commander's sight with x15 magnification incorporated into a No.21 Cupola – all intended to aid target acquisition and reduce engagement times.

The tanks were fully prepared by the end of October 1986 but because of their autumn commitments neither contending squadron (Badger Squadron of 2 RTR and B Squadron of The Royal Hussars) was able to take up the offer of two days familiarisation on the competition range at Grafenwohr before it was placed in quarantine on 1 January 1987. Severe weather during February and March restricted training further. On the 1 April the final entrant was chosen when The Royal Hussars were drawn out of the hat. Fatefully being the most disadvantaged of the two regiments, the best laid plans made in the wake of CAT '85 were completely undermined.

Following the selection of The Royal Hussars, all training resources were concentrated on B Squadron who set up permanent camp on Battlerun 9 at Hohne. This was laid out to represent the competition range but without any knowledge as to how the targets in the actual competition were to be presented. With increasing familiarity with the complexities of ICSS, some respectable results were achieved. Thus, when crews deployed to Grafenwohr for a 'mini-CAT' competition on a

² Named after the person who designed it – SSgt Charlie Chase of 4th/7th Royal Dragoon Guards, – the Chase Modification automatically closed the gun breech on operating the loader's firing guard which speeded up the loading procedure. Before it was installed the breech had to be closed manually.


The first purpose-built driver training tank for the British Army was completed and delivered by Vickers Defence Systems in 1990. The 17 Challenger Training Tanks or CTT provide realistic yet cost effective driver and maintenance training for both the Royal Armoured Corps and the Royal Electrical and Mechanical Engineers. (Simon Dunstan)



representative range in May, they compared favourably with the eventual American winners in the M1 and the Canadians in the Leopard CA1. It was at this stage that B Squadron, following the example of other teams, enlisted the services of an acclaimed sports psychologist to help prepare the crews for CAT '87. Imperceptibly, the original directive of the CGS of damage limitation was being forgotten. Under the tutelage of the sports psychologist, the ethos of winning became paramount and with it an exclusive elitism emerged among the competition crews who now adopted colourful cravats and badges while messing separately from support personnel. Within a short time, Hohne witnessed the spectacle of British tank crews humming mantras and dropping ping pong balls onto each other's stomachs to enhance inner awareness.

On 5 June, B Squadron of The Royal Hussars deployed from Fallingbostal to Grafenwohr; a distance of some 700 kms. The competition lasted from 15-19 June with each team being required to make three battleruns; one for each troop or platoon. The run consisted of three bounds with firing taking place while static on these and on the move between them. Targets were at ranges between 800 and 2000 metres. A successful engagement depended on individual tank accuracy and the rapid acquisition and allocation of targets. The objective was to hit the maximum number of targets but, with almost equal points being awarded for time of engagement, a very high premium was placed on speed. Each tank carried ten rounds of main armament and 250 rounds of machine

1:76 scale side view drawing of a Challenger Training Tank. (Tim Neate)



gun ammunition. The three tank troop was required to hit 24 targets with main armament and knock down 60 falling plates arranged in groups of ten; for four tank platoons it was 32 targets and 80 falling plates which statistically is marginally more difficult. A theoretical maximum of 22,600 points could be scored by each troop or platoon based upon

A Challenger 1 Mark 2 of 2nd Royal Tank Regiment moves off on a 'battle run' on the tank gunnery ranges at Hohnle during 1989. With a high reputation for gunnery, 2 RTR failed the cut for CAT '87 which was to have far reaching ramifications to the future of Challenger. Here, the L11A5 120mm with its thermal sight is shown to advantage. (MOD)



the targets hit, the time required and a bonus for unexpended ammunition.

Analysis of the performance of The Royal Hussars during training demonstrated that, in their modified Challengers, crews had the potentiality to achieve 22 hits out of 24 in a mean time of about 14 seconds to achieve scores of between 16,500 and 17,500; exactly what was required for the aim of damage limitation. Once again luck did not favour the British as The Royal Hussars were chosen to fire on the opening run of the competition with no knowledge of the course, whereas all the other teams were allowed to watch and assess the targetry and terrain. Their second run was to be on Wednesday and their third on Friday - the final day of the competition. It was decided that 3rd Troop should open the batting followed by 1st Troop on Wednesday, considered to be the weakest in the squadron, and 2nd Troop, who had shown the strongest performance, on Friday.

In the event, 3rd Troop's first run was entirely consistent with the predictions and, by firing methodically and accurately, 22 out of 24 targets were hit at an average time of 13.64 seconds giving a perfectly satisfactory score of 16,606. However, there had been mechanical problems with the presentation of some of the targets and 3rd Troop were offered a re-run on condition they sacrificed their original score. Having got a feel for the range, the squadron leader believed they could do better on a re-run although it would not take place until late on Wednesday. This meant that in effect 1st Troop was to open the batting which put them under considerable pressure as the Abrams and Leopard 2 teams achieved increasingly impressive scores.

Unfortunately so it proved on the Wednesday when accuracy was sacrificed for speed and, although 1st Troop achieved the fastest average engagement times of the four British runs at 11.7 seconds, seven targets were missed. With the troop communications being broadcast over the public address system, it became apparent that troop control had failed - one commander urging his crew to be faster immediately after a successful

three second engagement! With a mediocre score of 14,306 by 1st Troop, 3rd Troop tried to better its performance of Monday but to no avail. Again speed was the enemy of accuracy causing too many errors of lay and only 18 targets were hit as against 22 on their previous run, giving a score of 14,260 - the lowest in the competition so far.

By Friday, The Royal Hussars were lying at the bottom of the score sheet by a wide margin and this was the last opportunity to redeem themselves. 2nd Troop was therefore under



intense pressure. All began well but during the move from the first bound disaster struck. The loader in the troop leader's tank, having put a projectile into the breech, had to deal with a broken belt on the coaxial machine gun during firing on the move. Having tried but failed to resolve this problem he returned to the breech when the vent tube magazine fell off. By the time he had fixed this he was confused and loaded a second projectile, jamming the breech - such are the disadvantages of three piece ammunition. Despite hitting 19 targets out of 24, 3rd Troop could only achieve a meagre score of 13,673.

When compared with the winning team's score of 20,490, which incidentally is the highest ever in a CAT competition, the result was dismal. Beside himself with rage, the C-in-C BAOR departed in his helicopter. His entourage followed. By lunchtime, the highest ranking British officer remaining was a subaltern of The Blues and Royals tasked with public relations - not an enviable task in the circumstances. As for The Royal Hussars themselves, they were completely devastated but to their credit none blamed the tank itself. Within weeks, not a single troop leader in the CAT team remained in the British Army.

With its TISH clearly visible, a Challenger 1 Mark 2 kicks up the dust as it advances over the patched prairies at BATUS in Canada. The major shortcoming of TOGS on Challenger 1 is the problem of maintaining precise mechanical alignment of the TISH in its side-mounted barbette with the main armament. It is apparent how the vehicle's callsign on the side plates becomes totally obscured in such conditions. (MOD)

Percentage of Rounds that were Hits by Vehicle Type

	M1	LEO 2	LEO 1	M60	CHIEF/CHALLENGER
1985	75.66	70.89	64.86	62.5	61.04
1987	94.00	92.00	85.00	NA	75.00

Average Kill Times by Vehicle Type

	M1	LEO 2	LEO 1	M60	CHIEF/CHALLENGER
1985	10.23	11.93	16.22	14.10	13.00
1987	9.10	9.60	11.10	NA	12.61

The table on the previous page shows the relative performance of the contending MBTs at CAT '85 and '87.

These figures, however, do not fully reveal the complete superiority in the competition of those tanks equipped with a commander's panoramic sight and gunner's stabilised sight over those without when firing on the move; Abrams and Leopard 2 being twice as probable to hit a target at 88.5 per cent as against 43.5 per cent for Challenger. The ICSS fitted to the CAT modified Challengers incorporated an Independent Aiming Mark in the gunner's sight which attempted to replicate the effect but was not nearly as efficient as true stabilisation. This and a host of other factors touched on in this account militated against Challenger being able to shine during the CAT competition.

It is a measure of the success of the NATO alliance in maintaining the peace for over 40 years that the Canadian Army Trophy assumed such importance and came to be regarded as a valid operational test. Thankfully, there had been no wars to measure the relative effectiveness of all the current generation of MBTs but no manufacturer was slow to trumpet the success of his product following a CAT competition. The ever escalating cost of military equipments has made foreign sales a necessity in any weapons procurement programme. Despite vigorous sales campaigns in the Middle East in 1983, 1985 and again in 1987, the latter coinciding with CAT '87, there have been no foreign purchases of Challenger.

During the preparations for CAT '87, a total of 6,585 rounds of DS/T 120mm ammunition was expended at a cost of approximately £1.9m (\$2.9m). Competition crews each fired in excess of 500 rounds during training which was well beyond the 134 permitted by the rules, but the stakes were high and the cost represents approximately the price of one MBT; money well spent if foreign sales had ensued. As to the rules of the competition, each nation interprets them as they will; whether it be the grizzled gunnery instructor who appears in the turret of a young con-

A Challenger 1 Mark 2 of B Squadron, The Royal Scots Dragoon Guards, surges over an earth rampart on the Sennelager training area in West Germany in 1989. In the same year during Exercise White Rhino, German farmers tried to block the passage of tanks with similar barriers to disrupt military exercises as the Green movement became more prevalent. To 60 tonnes of Challenger at speed they proved to be of little impediment but a year later, in the face of Iraqi defensive berms, the need to protect the lower hull front from short range anti-armour weapons as the tanks negotiated such obstacles led to the introduction of Explosive Reactive Armour on the toe and glacis plate of Challenger. (MOD)





A group of Challenger 1s shelter in a fold in the ground on the wide open prairie at BATUS in Canada - those of 1st Armoured Squadron (white fume extractors and white stripes on rear bazooka plates) are at 'check fire' with their main armaments fully elevated while the one at full depression is checking the Muzzle Bore Sight. In the foreground is a Challenger 1 of 2nd Armoured Squadron which can be identified by the white border around the call sign.
(Media Ops Land Command)

script crew or those who surreptitiously video the targets and layout of the competition range after it has been placed in quarantine in order to reprogramme the tank gunnery simulators for their teams. Be that as it may, no amount of splanetic apoloia in the letters column of *The Daily Telegraph* could escape the fact that the complexity and poor ergonomics of the turret system of Challenger led to unsatisfactory human performance on the day.

CHALLENGER TO CHALLENGER 2

At the beginning of 1987, it was still the intention of the British Army to retain a mixed fleet of some 1200 Chieftain and Challenger MBTs until the turn of the century when it was anticipated they would be superseded by yet another Anglo-German collaborative venture which was begun in the early 1980s. This project, known as the 'FMBT 2000', was based on the prospect that both countries would need to replace their current designs at about the same time. Development centred on a new technology tank gun using either solid or liquid propellant, and even more advanced technologies such as an electro-magnetic rail gun were being addressed. However, it became evident that a liquid propellant gun could not be fitted to a tank by the year 2000.

Even before it entered service, the limitations of Challenger's fire control system and the need to modernise its turret systems had been recognised. Accordingly, a series of extensive modifications had been set in hand which was known as CHIP or the Chieftain/Challenger Improvement Programme. The development of a new high pressure 120mm rifled gun, the XL-30, and high performance ammunition, including Depleted Uranium (DU) penetrators, was also progressing under the designation CHARM or Chieftain/Challenger Armament.



With the essential brew of tea to hand, the commander of a Challenger 1 Mark 3 of 2 Troop, B Squadron, The Queen's Royal Hussars, directs his driver to a new fire position during Exercise First Crusade on Salisbury Plain in October 1995. The Mark 3 variant has a revised internal layout and armoured charge bins for greater protection of the two-piece ammunition propellant. As the final production model, 156 Challenger 1 Mark 3s were built with the last deliveries to the British Army being made in 1990. (Simon Dunstan)


Originally both programmes were to be implemented on Chieftain and Challenger, although it was realised that retaining Chieftain into the '90s was increasingly risky in face of the improvements in Soviet tanks. For this reason Chieftain separately underwent an uparmouring programme known as Stillbrew and was fitted with TOGS to give it a true night-fighting capability.

However, the success of the plan for a CHIP/CHARM improved Chieftain to soldier on through the '90s depended on it being replaced by a new tank before the year 2000 but this was now highly unlikely. It was at this stage that Vickers Defence Systems which had recently acquired the former Royal Ordnance factory at Leeds with its excess manufacturing capability offered to build a replacement for Chieftain on the basis of a fixed price contract; the design being essentially the combination of a Challenger hull and automotives with the turret of the Vickers Mark 7 private venture export model MBT. The new model was somewhat confusingly designated Challenger 2 Mark 2.

It was against this background that Challenger shortly afterwards entered CAT '87 when it was seen to perform even worse than Chieftain. Not only was the Royal Armoured Corps (RAC) shown in a poor light but it also raised doubts about its operational efficiency and the efficacy of its equipment. In the immediate aftermath, several senior officers within the RAC tendered their resignations but these were refused pending a detailed analysis of Challenger during CAT '87. A formal inquiry was convened at the RAC Gunnery Wing at Hohne on 9 July which examined every aspect of crew and tank performance. Its report found that there had been many reasons for the failures during CAT '87 including mistaken selection procedures for the competition team; the extensive training commitments for British armoured regiments as against other opposing teams who in most cases trained almost exclusively for CAT for seven months or more; the totally inadequate provision of training simulators and coaching aids; the size of troop with only three tanks proved to

1: Challenger 1 Mk. 2, C Sqn.,
The Royal Hussars, Fellingbostel,
BAOR, West Germany,
17 September 1966


1a



1b




2a



2b

2: Challenger 1 Mk. 3, D Sqn.,
The Royal Scots Dragoon Guards (Carabiniers
and Greys), 7th Armoured Bde. Group, Saudi
Arabia, 14 November 1990

Challenger 1 Mk. 2 Command Tank, Regimental HQ, 14th/20th King's Hussars, 4th Armoured Bde., 1st (UK) Armoured Div., Kuwait, 28 February 1991



Challenger 1 Mk. 3, C Sqn., Queen's Royal Irish Hussars, 1 Staffords Battle Group,
7th Armoured Bde., 1st (UK) Armoured Div., Kuwait, 28 February 1991



a

b



CHALLENGER I MK.3


**COMMAND TANK, BRIGADE HEADQUARTERS,
7TH ARMoured BDE, 1ST (UK) ARMoured DIV,
SOUTHERN IRAQ, 26 FEBRUARY 1991**

SPECIFICATIONS


Crew: 4 (Commander, loader, gunner and driver)
Weight: Approx 60 tonnes
Length gun forward: 11.55m
Height to top of Commander cupola: 2.88m
Width: Overall 3.52m, over tracks 3.42m
Ground clearance: 0.5m
Ground pressure: At battle weight 0.9Kg/cm²
Road speed: Up to approx. 60km/h
Vertical obstacle: 0.9m
Max gradient: 30°
Trench crossing: 3.15m
Shallow fording: 1.07m
Engine: Perkins Conдор 12 cylinder 60 V direct injection, 4 stroke diesel, compression-ignition
Capacity: 26.1 litres, rating 1200 BHP (895kW) at 2300 rpm (BSS), 11296 BHP (DIN)
Generator: 500 amp
Gearbox: TN37 epicyclic - 4 forward gears, 3 reverse gears, automatic transmission with torque converter
Suspension: Hydrogas type
Main armament: Ordnance breech loading 120mm Tank gun L11A5
Ammunition: Minimum of 44 projectiles consisting of APDS, HESH, SH4 Practice, DS/T Smoke, 42 charge containers each holding one APDS or two HESH charges
Coax MG: 7.62mm calibre TRL842

KEY


- | | |
|---|---|
| 1. D10 communication cable drum | 23. Symbology processing unit (Sperw) |
| 2. Drive sprocket | 24. Turbine services junction box |
| 3. Final drive | 25. Turbine batteries hatch |
| 4. Main brakes (power valve) | 26. 120mm Gun breach |
| 5. 40-gallon auxiliary fuel drum | 27. VIC/ISS Reactor |
| 6. External tool storage | 28. 30-Pound ready rack |
| 7. Gun clamp | 29. NBC control panel |
| 8. Transmission covers | 30. 6-Pound ready rack |
| 9. Radiator | 31. LB 7.62mm Coaxial machine gun |
| 10. Air charge transmission oil cooler | 32. Interface box 2 (Radio) |
| 11. Turbo-charger | 33. Crew box 2 (Radio) |
| 12. Induction heated heater | 34. Camouflage net storage basket |
| 13. Gun depression stop rails | 35. Smoke grenade dischargers |
| 14. Coolant level inspection hatch | 36. Fire extinguishers |
| 15. GUE (auxiliary engine) oil level inspection hatch | 37. Instrument panel |
| 16. Main engine | 38. Steering levers |
| 17. TOGB compressor unit | 39. Handbrake |
| 18. Commander's storage bin (from Forest Scout Car) | 40. Projectile storage rack |
| 19. TOGB batteries | 41. Horn (on side of headlight cluster) |
| 20. Commander's sight | 42. Driver's seat (closed down) |
| 21. Commander's position | 43. Clear selector |
| 22. GPS Transponder | 44. Front fender |



- | |
|----------------------------------|
| 45. MRS mirror mount |
| 46. Fume extractor |
| 47. L11A5 120mm Main armament |
| 48. Chobham armour side panels |
| 49. Fuel filler cap (2 per side) |
| 50. Transmission heat exchanger |



1: Challenger 1 Mk. 3 Control Tank, D Sep., Queen's Royal Irish Hussars Battle Group, 7th Armoured Bde., 1st (UK) Armoured Div., Southern Iraq, 25 February 1991




2: Challenger Armoured Repair and Recovery Vehicle, 6th Forward Repair Group, Royal Electrical and Mechanical Engineers, 4th Armoured Bde., 1st (UK) Armoured Div., Kuwait, 4 March 1991

Challenger 1 Mk. 2, 1st Armoured Squadron, The Queen's Royal Lancers, BATUS, Canada, June 1994



1: Challenger 1 Mk. 3, B Sqn., The Queen's Royal Hussars, IFOR, Operation Resolute, Central Bosnia, 11 January 1996



2: Challenger 1 Mk. 2 Command Tank, Command Troop, HQ Sqn., 2nd RTR, 7th Armoured Bde., 1st (UK) Armoured Div., Poland, 12 September 1996

be disadvantageous psychologically and the use of prototype equipment for the competition was deemed to be a mistake, both with the Improved Computerised Sighting System and the x15 magnification commander's sight which compromised observation of the fall of shot. However, most of these were peripheral and the report concluded that the

fundamental cause of the persistently disappointing scores in CAT was the complexity, poor ergonomics and susceptibility to failure of the turret systems of Challenger and Chieftain, compounded by the use of three-piece ammunition leading to human error. This placed British crews under far greater strain than others and imposed an intolerable training load which was exacerbated by the deplorable lack of simulators.

The outcome of the competition was known in the highest political circles and leading questions were being asked about British tank procurement procedures. The concerns in government led to various demonstrations of Challenger together with Abrams and Leopard 2 which proved irrefutably that it was seriously deficient when firing on the move against moving targets. With the prospect of any future main battle tank incorporating advanced technology receding well into the 21st Century, it was decided that a replacement for Chieftain had to be pursued separately and as quickly as possible. Accordingly, a paper was prepared for the Equipment Policy Committee of the Ministry of Defence outlining the options available for a replacement for Chieftain. These included the current Challenger; the Vickers Defence Systems proposed Challenger 2 Mark 2 together with a Mid-Life Improvement Programme for the existing Challenger fleet and two foreign options which were improved versions of the Abrams M1A1 and Leopard 2.

In November 1987, the Equipment Procurement Committee endorsed Staff Requirement (Land) 4026 for the Chieftain replacement programme. This began with a preliminary assessment of the formal proposal by Vickers Defence Systems for its Challenger 2 Mark 2, which for the sake of simplicity the Ministry of Defence called Challenger 2 while the existing MBT became Challenger 1, in comparison with the Abrams



V5 - the fifth Challenger 2 prototype churns through the mud during a demonstration before the Defence Minister of Saudi Arabia on Salisbury Plain in 1993. This model features TECs or Thermal Exhaust Cows which are a wartime fitting to reduce the tank's thermal signature. (MOD)

In the aftermath of the Gulf War of 1991, Challenger 2 was presented to various Middle Eastern armies leading to the purchase of 18 Challenger 2 MBTs, four CRAAVs and two Driver Training Tanks by Oman in 1993. Below the registration number 06SP95, this Challenger 2 prototype bears the Arabic inscription 'Desert Defender'. (Dennis Lunn MBE)





A production model Challenger 2 is put through its paces by ATDU during acceptance trials at Bovington. The commander has a gyroscopically-stabilised, panoramic sight with an integral laser rangefinder, enabling him to acquire and range targets independently of the gunner. For improved alignment, the TOGS is mounted above the main armament in an armoured housing. (Media Ops Land Command)

M1A1 and Leopard 2 then in-service with their respective armies. Neither of the latter as they existed at the time fully met the British requirements for a Chieftain replacement. However, in the wake of CAT '87, there was considerable dissatisfaction with Challenger, both in the upper reaches of government and within the Royal Armoured Corps. Since doubts had been expressed at the level of armour protection of Leopard 2, a strong faction within the army declared an interest to forego any further delays and procure the Abrams M1A1 which was seen to be a mature and proven design. To others, for the country that invented the tank, the concept of not buying a British tank was unthinkable.

In the event, extensive comparative trials ensued of four contenders for the Chieftain replacement programme – Challenger 2; Abrams M1A2; Leopard 2 (Improved) and the Leclerc – all of which proved to be highly capable with each excelling in one aspect or another while a final decision was to be made by the Equipment Procurement Committee in December 1990.

Once again world events were to impinge on British tank procurement plans. Whereas Challenger was born out of the fall of the Shah of Iran, the collapse of the Warsaw Pact resulted in 'Options for Change' which, under Treasury demands to provide a 'peace dividend', dramatically reduced the number of MBTs to be procured. Initially the intention had been to replace Chieftain on a one-for-one basis and interoperability with the rest of NATO on a purchase of over 500 MBTs was a major factor, with standardisation on the 120mm smooth bore gun being desirable. At this number, the economy of scale favoured the Abrams whereas, on the other hand, co-production of Leopard 2 would allow the British foreign sales to countries denied to the FRG. However, Iran's traditional enemy Iraq had become the focus of world attention following its successful invasion of Kuwait and the deployment of 1st (UK) Armoured Division to the Gulf region deferred any decision until such time as

the Gulf War allowed an assessment of the battle performance of Challenger and Abrams.

In the event Challenger went to war and was not found wanting. In no small part this was due to VDS and other major contractors, such as Barr and Stroud; David Brown; Perkins; Marconi; Commercial Hydraulics et al, providing the expertise and support that allowed an availability rate of over 90 per cent to be achieved throughout the campaign. It proved once again that British industry could produce the goods given that the financial restraints imposed by the Treasury were removed for the duration of the war.

In what has been termed 'the only tank battle to be fought on British soil', Vickers Defence Systems were finally awarded a contract at midnight on 28 June 1991 for 127 Challenger 2 MBTs and 13 Driver Training Tanks. This was the minimum number of tanks that was necessary to maintain a viable production line at a rate of approximately 35 tanks per year. With a total value of about £500million (\$758m), the contract included an integrated Logistic Support Package whereby VDS was responsible for all aspects of introducing Challenger 2 into service with the first two armoured regiments (Royal Scots Dragoon Guards and 2 RTR) to be equipped with the new MBT.

At the same time, approximately £275million (\$415m) was budgeted for a Challenger 1 Mid-Life Improvement Programme which was also to be managed by VDS. Various measures were proposed from rearming Challenger 1 with the L30 high pressure gun to replacing the complete turret with that of Challenger 2. However in the further round of defence cuts known as 'Front Line First', the Ministry of Defence abandoned the plan to upgrade the Challenger 1 fleet and, instead ordered an additional 259 Challenger 2 MBTs from VDS. Furthermore the Royal Armoured Corps was reduced from 13 tank regiments to eight with two in Britain and six in Germany. In turn, each tank regiment was reduced to 38 MBTs as against 50 in the previous organisation, with two at regimental headquarters and three squadrons each with four troops of three tanks. The new composition of the Type 38 organisation was designed to preserve more of the army's famous cavalry regiments in being rather than for any particular tactical considerations. Thus, by the turn of the century, the British Army is scheduled to have a total of 386 Challenger 2 MBTs with 304 in frontline service and the remainder being used for training and war reserves. The Challenger 1 fleet will be disposed of although a number of hulls may be retained and converted to combat engineer vehicles capable of the same degree of mobility as the Challenger 2 MBTs they are required to support.

For export, VDS offers an improved model of Challenger 2 which is named Desert Challenger 2, reflecting its most likely market, or latterly Challenger 2E - the 'E' standing for 'export'. Combining the best elements available, Challenger 2E is less than 50 per cent British, as it comprises German automobiles of an MTU 1500 bhp diesel engine and Renk transmission; French sights and a North American fire control system. When built to the British concept of firepower and survivability, this is a truly formidable MBT. (VDS)





Once the 'Quayside Modifications' had been completed, the Challengers of 7th Armoured Brigade Group deployed to the desert to begin training in the area of Al Fadhili - here 2 Troop, A Squadron of The Royal Scots Dragoon Guards manoeuvres at speed during one of the innumerable demonstrations for the world's press in the first weeks following their arrival in the Gulf region. (SCOTS DG)

THE GULF WAR - OPERATION DESERT SABRE

In 1990, following the final deliveries of Challenger, the British Army had a total of 1202 gun tanks in service, comprising 752 Chieftains, 420 Challengers³, and 30 Centurions AVRE with the Royal Engineers. At this time the Royal Armoured Corps comprised 17 armoured regiments with the seven equipped with Challenger being stationed in Germany with 1st, 3rd and 4th Armoured Divisions of 1st British Corps as one of the four corps of the Northern Army Group within NATO. There were two forms of tank regiments; the Type 57 in armoured brigades and the Type 43 in mechanised brigades. A Type 57 armoured regiment comprised four squadrons, each of four troops of three tanks with two tanks in squadron headquarters and one in regimental headquarters. A Type 43 armoured regiment was similarly organised but with only three squadrons.

Following the Iraqi invasion of Kuwait on 2 August, the British government supported the United Nations coalition forces tasked with responding to such blatant aggression against another sovereign state by deploying 7th Armoured Brigade from Germany to Saudi Arabia. Retaining the title of 'The Desert Rats', the brigade comprised two armoured regiments equipped with Challenger 1, The Royal Scots Dragoon Guards (Carabiniers and Greys) (SCOTS DG) and The

³ The Challenger fleet comprises 253 Challenger 1 Mark 2 of which 7 are command variants; 34 control and 212 gun tanks, plus 156 Challenger 1 Mark 3 of which 4 are command, 22 control and 130 gun tanks. The remainder are reworked prototypes used for driver training, 'pony and trap' models for public display and reference vehicles at various establishments. In addition there are 17 Challenger Training Tanks and 81 'Rhino' CRARRVs.

Queen's Royal Irish Hussars (QRH), and an armoured infantry battalion, 1st Battalion, The Staffordshire Regiment (1 Staffords) equipped with Warrior. There ensued a hectic period of preparation at Fallingbommel to bring the various units up to wartime establishment. By the end of October, 7th Armoured Brigade Group had arrived at Al Jubayl on the eastern coast of Saudi Arabia where the brigade came under the operational command of the 1st (US) Marine Division of the 1st Marine Expeditionary Force.

From the outset the decision was taken to equip the tank regiments with the Mark 3 variant of Challenger with its armoured charge bins, for the greater protection they provided to the crews, while the Mark 2s were cannibalised for spare parts. As the tanks arrived in the port of Al Jubayl, they underwent a series of 'Quayside Modifications' to enhance reliability in the desert conditions. These were carried out by REME personnel and an Engineering Support Team composed of engineers from the principal contractors responsible for Challenger including Vickers, Perkins, David Brown, Barr and Stroud and Marconi. Subsequently, the team supported the armoured regiments in the desert by instructing crews in the prescribed procedures for vehicle operation and maintenance.

Once these modifications were complete, the tanks deployed to the desert and training began in earnest in the area of Al Fadhili with gunnery being performed on the Jerboa Range. On 16 November, 7th Armoured Brigade Group was declared operational with the task to prepare for counter-penetration operations in support of 1st Marine Division. In some minds within the US high command, there remained lingering doubts about the efficacy of British equipment, particularly Challenger with its legacy of CAT '87, but these were dispelled after a series of dramatic live-firing exercises on the Devil Dog Dragoon Ranges. As planning began for offensive operations to liberate Kuwait, it was realised that 7th Armoured Brigade Group was likely to be in action in support of the US Marines against heavily fortified defensive positions culminating in fighting in the streets of Kuwait City. Accordingly, the tanks would be facing a gamut of anti-armour weapons at short ranges so it was decided to increase the armour of the Challengers along the hull sides, to protect those areas where the ammunition propellant was stowed in the fighting compartment, and over the hull front to give the driver greater protection. Other modifi-



One of several modifications devised for Challenger during Operation Granby was the installation of a smoke generating system. A pump mounted in a jerry can on the rear hull plate fed diesel from the two reserve fuel drums into the exhaust producing dense white smoke. This was impenetrable to Iraqi observation devices but Challengers could shoot through it using their thermal imaging sights of TOGS. (QRH)

Once training began in earnest, tank crews soon discovered the problems of operating in the featureless desert. Not least of these was 'sabhka' where the desert sand formed a thin layer over salt marsh beneath with the consistency of wet cement. Once a vehicle broke through the crust it soon became bogged - here three Challengers of B Squadron, SCOTS DG, are being retrieved in the first operational recovery ever undertaken by a CRAARV. (Will Fowler)





cations included extra fuel drums and a smoke generating system which injected diesel fuel directly into the engine exhaust; both of these devices having been used on Soviet tank designs for many years.

Although each tank regiment was supported by Chieftain armoured recovery vehicles, the Challenger Armoured Repair and Recovery Vehicle (CRARRV) was rushed into front line service some seven months before it was due to join the British Army. The first four production models (Faith, Hope, Charity and Big Geordie!) were despatched on 24 September directly from the Vickers factory in Leeds to 7th Armoured Brigade Group in Saudi Arabia. In all, 12 CRARRVs were deployed in support of 1st (UK) Armoured Division. Divided between 4th and 7th Armoured Brigades, they served with the Forward Repair Groups rather than at regimental level. Overall they covered some 19000 kilometres, 7000 kms of which were while towing other AFVs. During the course of the campaign the CRARRVs required five pack changes, giving a mean distance between failures of almost 4000kms which, incidentally, was the original General Staff Requirement for Challenger.

On 22 November, the decision was taken to increase the strength of British ground forces with the addition of 4th Armoured Brigade and other support elements to form 1st (UK) Armoured Division which was transferred from operational control of the Marines to the US Army VII Corps to participate in the major offensive against the Iraqi Army. With two armoured infantry battalions, 1st Battalion, The Royal Scots, and 3rd

1:76 scale side view drawings of a Challenger 1 Mk. 3, and below, Challenger 1 Mk.3 (uparmoured). (Tim Neate)





With the armoured door of the TOGS barquette open, a Challenger 1 Mark 3 of The Queen's Royal Irish Hussars displays the full array of supplementary armour fitted to the Challengers of 1st (UK) Armoured Division during Operation Granby, with Chobham armour panels along the sides and Explosive Reactive Armour (ERA) on the glacis plate and toe. (QRIH)

A further modification made to Challengers during Operation Granby was the fitting of two 45-gallon fuel drums at the rear. Here, the crew of a Challenger 1 Mark 3 of B Squadron Royal Scots Dragoon Guards manhandles a fuel drum into the 'upright position' for gravity feed of diesel into the main fuel tanks. This device increased the combat range by some 100 kilometres. (SCOTS DG)



Battalion, The Royal Regiment of Fusiliers, and a single armoured regiment, 4th Armoured Brigade was in fact a mechanised brigade. For this reason, the armoured regiment, 14th/20th King's Hussars, was Type 43, and to bring it up to a wartime establishment of 58 Challengers it was reinforced by A Squadron, The Life Guards, as a complete sub-unit. As many of the regiment's tanks were Mark 2s, new armoured charge bins were designed and fitted in theatre raising them to Mark 2 (ACB) standard; arguably this variant was better protected than the Mark 3 since its armoured bins contained the propellant charges

in twos or 'doublets' rather than in the 'triplets' of the Mark 3.

While these protective measures did much to boost the morale of the crews and instil confidence in the survivability of their tanks, enhancements were made to the offensive capabilities of Challenger with the introduction of a highly potent armour-piercing round. Under the codename Jericho, the L26A1 APFSDS round incorporating a depleted uranium penetrator was manufactured by Royal Ordnance as a counter to the T-72M that equipped the Iraqi Republican Guard. With its low silhouette, high speed and powerful main armament of the 125mm D-81 TM (2A46) gun, the T-72M was deemed to be the only serious threat to Challenger on the battlefield. The new round was coupled with an improved propellant charge, the L14A1, which gave both better performance and greater safety. Each Challenger was issued with approximately 12 L26 rounds to be used exclusively against T-72Ms. In the event, no T-72Ms were encountered by 1st (UK) Armoured Division during the war.

However, the two aspects of Challenger that proved to be fundamental to success on the battlefield were TOGS and GPS. The superiority of the Thermal Observation and Gunnery System of Challenger over the sights and night-fighting capabilities of the Soviet tanks that equipped the Iraqi Army was fully appreciated before the war and determined the tactics for tank vs tank engagements. In essence, TOGS allows target acquisition and engagements in open terrain out to 3000 metres - well beyond the capacity of the Iraqis. Accordingly, all engagements were to be at long ranges and, if the enemy closed to

within 1500 metres, the Challengers were to fall back to maintain their long range advantage. In the event, the weather was so foul during the conflict and the enemy's tanks were so predominantly static that these tactics were not applicable, although one SCOTS DG Challenger had a successful engagement with a first round hit against an Iraqi tank at



The final preparations are made to a Challenger 1 Mark 3 of the Royal Scots Dragoon Guards in the days just prior to the land offensive. With a Cross of St Andrew on the TOGS barrette, this Challenger belongs to C Squadron whose tanks featured a white painted fume extractor; an identifying feature commonly used at BATUS. Readily apparent behind the commander's cupola is the TOGS indicator which being circular denoted the third troop in the armoured squadrons of SCOTS DG. (SCOTS DG)

Under the leaden skies that were typical throughout the land offensive, a Challenger 1 Mark 3 of A Squadron, 14th/20th King's Hussars, advances at speed. Note the solid black triangle on the forward Chobham armour panel designating A Squadron and the black painted fume extractor which denotes 4th Troop; the other troops each having the requisite number of rings. (MOD)

4100 metres. The second battle winner was the GPS (Global Positioning System) navigation aid which for the first time in warfare allowed units to determine their exact position with a high degree of confidence, particularly in the featureless desert terrain of southern Iraq. Two types of GPS, Magellan and Trimble, were issued to

British units on a typical scale of five per tank squadron. The system was highly efficient as long as sufficient satellites were in alignment for interrogation and it allowed allied forces to manoeuvre freely around known enemy fixed positions and attack from the least expected quarter. At the same time, knowledge of the whereabouts of neighbouring friendly units was a major factor in reducing the incidence of fratricide or 'blue on blue'.

The use of GPS in combination with TOGS gave the battlegroups of 1st (UK) Armoured Division a significant advantage over the enemy as Challengers led repeated day and night attacks with the armoured infantry in their Warriors against a succession of Iraqi brigade sized positions, each objective being codenamed by a particular metal such as Copper, Bronze, Zinc, Steel et al. Within 100 hours the Iraqi Army had been routed by the coalition forces. However, to the trooper in a Challenger tank or the rifleman in the back of a Warrior, having endured weeks of discomfort in the desert and suffered multiple injections against the appalling threat of chemical and biological agents in the certain knowledge that he was facing one of the largest armies in the world which had had many months to prepare defensive positions, all these factors remained an unknown quantity as they crossed the border into Iraq. It is a tribute to the professionalism of the soldiers of the British Army that to a man they faced this prospect without demur and prevailed, while retaining an essential humanity towards the enemy soldiers they fought. Part of this professionalism was an unstated confidence in their equipment, be it Challenger or Warrior, both of which are demanding vehicles to operate but once mastered they have few equals to match them. In the words of Brigadier Patrick Cordingley DSO, Commander 7th Armoured Brigade, "I have always said that Challenger is a tank built for war and not competitions".



THE PLATES

A1: CHALLENGER I MK. 2, C Squadron, The Royal Hussars, Fallingbostal, BAOR, West Germany, 17 September 1986 (Sgt. 'Pink' Penkethman)

The Royal Hussars were the first armoured regiment to be equipped with Challenger and this one is finished in the standard British Army camouflage scheme of matt black irregular stripes over the green base colour. It also features low visibility callsigns; in this case 21 within a circle denoting the Troop Sergeant of 2 Troop, C Squadron. The callsign is painted on each turret side and on a plate attached to the turret basket facing to the rear. **1a** The regimental crest of The Royal Hussars adorns the door front of the TOGS barbette. **1b** On the lower hull front is the bridging classification sign of a small black 60 within a solid grey circle, indicating the vehicle's weight in metric tonnes. Above it is the vehicle registration number 35KA68 inscribed in white on a black rectangle. This is repeated on the rear hull plate beside the right hand light cluster; as viewed, with the letter and number groups arranged vertically. Below the towing bar is a white square with the tank callsign and squadron marking superimposed in black, which can be illuminated at night for vehicle identification by personnel on the ground; for instance during night replenishment. This is common to all Challengers and applies to all the colour plates in this book. It also acts as a convoy distance marker at night. On the left rear hull plate above a jerry can is a first aid box indicated by a red cross on a white solid circle. This Challenger is depicted on Battle Run 9 at the Hohne Ranges near Fallingbostal with Prime Minister Margaret Thatcher in the turret and a Union Flag flying from the radio antenna. During a visit with Chancellor Helmut Kohl, she witnessed a firepower demonstration by a squadron of Challengers and a company of Leopard 2s. The two leaders then each climbed aboard one of their nation's respective MBTs and fired one round each at a target down range: both being successful much to the organisers' relief. Following her visit, the PM maintained a keen and inquiring interest in all matters relating to Challenger and the development of its successor.

Although impressive rates of availability were achieved during the Gulf campaign, this has not necessarily been the case in BAOR where the dearth of spare parts and lack of track mileage for MBTs has on occasions reduced the availability of Challenger to less than 20 per cent. This has been exacerbated by the reduction in the number of training areas in Germany which means that many MBTs are confined to their hangars or tank parks. (Simon Dunstan)

A2: CHALLENGER I MK. 3, D Squadron, The Royal Scots Dragoon Guards (Carabiniers and Greys), 7th Armoured Brigade Group, Saudi Arabia, 14 November 1990 (Lt. Angus Fraser)

Following several weeks of troop, squadron and regimental training, 7th Armoured Brigade Group was declared operational on 16 November 1990 after a major exercise in the area of Jebel Nufayl. Participating in the FTX, this Challenger 1 Mark 3 belongs to the Troop Leader of 3 Troop, D Squadron, SCOTS DG indicated by the white stencilled callsign on the forward bazooka plate on each side of the tank. The callsign Three Zero is repeated on a metal plate attached to the rear of the turret with the figures and stencilled rectangle painted in yellow on a black background. On the radio antenna is a piece of tape; one of several early measures to identify a troop leader. **2a** Behind the commander's cupola is a TOGS indicator - this one is circular when viewed from any direction. In SCOTS DG, it indicates 3 Troop and is intended to be visible at night through TOGS to aid identification of the various sub-units. Particular to D Squadron is the painting of a white stripe down the middle of the driver's hatch as a reference for the centre line of the vehicle when closed down. Like several young subalterns in the cavalry regiments deployed on Operation Granby, this troop leader was determined to acquire an Arab polo pony and brought his polo sticks just in case, one of which is stowed in the turret basket. In a similar vein the tank, whose registration number is 79KF22, is named DIOMEDES painted in black on the hull sides beside the driver (**2b**) - Diomedes who, in Greek legend, was a hero of the siege of Troy second only to Achilles in bravery or, in the Twelve Labours of Hercules, Diomedes was the king of the Bistones who owned horses which were fed on human flesh. Once vanquished by Hercules, Diomedes was given to his own mares to be eaten which, in the context of the Gulf War, is possibly more appropriate. However, the squadron leader, Major 'Jacko' Page, on attachment from The Parachute Regiment, did not approve of such embellishments and the name did not last beyond the week. Similarly the polo sticks did not survive beyond Concentration Area Keys.





B: CHALLENGER 1 MK. 2 Command Tank, Regimental Headquarters, 14th/20th King's Hussars, 4th Armoured Brigade, 1st (UK) Armoured Division, Kuwait, 28 February 1991 (Lt.Col. Mike Vickery)

'EMPEROR' is the traditional name given to the commanding officer's tank of the 14th/20th King's Hussars. It derives from the Battle of Vittoria in 1813 during the Peninsular War when the 14th Regiment of (Light) Dragoons captured the coach of King Joseph Buonaparte as he fled the battlefield. Among the spoils was an item described as "a silver utensil" which was in fact His Majesty's solid silver chamberpot. This gave rise to the regiment's nickname thereafter of 'The Emperor's Chambermaids', although the contemporary sobriquet is 'The Hawks'. The chamberpot has been preserved ever since in the Officers' Mess and does duty on special occasions as a 'loving cup' with the consumption of copious quantities of champagne. Bearing the registration number 36KA34, EMPEROR was one of only a few Mark 2 Challengers in the Gulf theatre that were not fitted with Armoured Charge Blins before the war began. As the armoured regiment within 4th Armoured Brigade it carries the black jerboa brigade insignia on the TOGS barbette. On all quarters it displays the inverted



'Absolute', a CRARRV of A Squadron, King's Royal Hussars, turns off the 'Panzerstrasse' to be replenished with fuel during an exercise on the Hohne/Bergen ranges in June 1995; lashed to its hull roof is a burnt-out auxiliary engine which it has just removed from a Challenger MBT. The CRARRV is highly regarded by REME personnel who have christened the vehicle 'Rhino' which has been adopted as its official name. (Simon Dunstan)

black V mutual recognition device of the coalition forces and, on the sides and turret rear, the callsign One One Bravo, denoting the commanding officer. Accordingly, the EMPEROR is a command tank with a three-radio fit, including BID for secure clear speech communications with higher headquarters which proved to be of a significant factor in the successful conduct of the fast-moving land offensive. Draped over the top of the turret rear is a fluorescent orange air recognition panel and forward of that is the transponder stalk of the Trimble GPS navigation aid which was such a vital asset in the featureless desert; note the top of the device is painted white. On each forward Chobham armour side panel is the unit code 1/1/HQ - the first figure denotes 4th Armoured Brigade; the second the 14th/20th King's Hussars as the senior regiment within the brigade and finally the sub-unit within that regiment. **A** Painted in red on the fume extractor of the main armament are silhouettes of the enemy vehicles destroyed by the EMPEROR during the 100-Hours War; EMPEROR's contribution to the regimental 'gamebook' being eight T-55s and ten other vehicles including a BRDM-2 which was about to engage the Hawks with Sagger missiles before it was destroyed by One One Bravo.

In January 1996, two armoured squadrons and a headquarters squadron of The Queen's Royal Hussars deployed to Bosnia as part of the British contingent to the NATO Implementation Force or IFOR. DROITWICH, the tank illustrated in Plate G1, heads a column of AFVS through an area of devastation at Mrkonjic Grad in the first patrol conducted by the Challengers of The Queen's Royal Hussars. (Media Ops Land Command)

C: CHALLENGER I MK. 3, C Squadron, Queen's Royal Irish Hussars, 1 Staffords Battle Group, 7th Armoured Brigade, 1st (UK) Armoured Division, Kuwait, 28 February 1991 (Sgt. Tony Stirling)

When the Gulf crisis erupted on 2 August 1990, the QRIH had only recently joined 7th Armoured Brigade in Germany, having been stationed at Tidworth in UK equipped with Chieftain MBT. Accordingly they were new to Challenger and were not scheduled to be fully operational until April 1991. Thus when 7th Armoured Brigade was deployed to the Gulf, the regiment was augmented by a complete squadron of 17th/21st Lancers who had served on Challenger for several years. To benefit from this experience, a formed troop of 17th/21st Lancers was attached to each squadron of the QRIH as their fourth troop. Four One within a circle denotes the Troop Sergeant's tank of 4 Troop, C Squadron. The latter, together with B Squadron, SCOTS DG, were detached from their parent regiments to form the tank element of 1 Staffords Battle Group. Originally named CRAIGAVON on the hull sides beside the driver's position, the name was not reapplied on the Chobham armour side plates. Instead the unit code 2/2/C is painted on the forward Chobham plate; the first 2 denoting 7th Armoured Brigade; the second 2 the QRIH as the second senior regiment within the brigade and C indicating C Squadron. This unit code is repeated on the sides of the rear fuel drums. A On each of the second Chobham armour side plates is a zap code with the crew names and their respective functions, a practice peculiar to the QRIH. Behind that is the black chevron and vehicle callsign, both of which are also painted on the rear fuel drums as they are on the turret sides and rear. On the other side of the turret, the callsign Four One within a stencilled circle is painted on the Ferret storage bin behind the TOGS barrette with the black chevron on the side of the TOGS compressor unit. Behind the commander's cupola is a TOGS indicator which being circular denotes C Squadron; A Squadron being triangular, B Squadron square and D Squadron rectangular, whereas in SCOTS DG the shapes applied to the troops within each squadron. With its registration number 64KG94, this Challenger 1 Mark 3 was commanded by a highly experienced gunnery instructor. Nine targets were engaged during the war of which eight were hit; the one miss being due to a wayward laser rangefinder. One T-55; three MTLBs and a trench system were destroyed. B Unwilling to lose their identity as 'The Death or Glory Boys', all the tanks of 17th/21st Lancers carried the regimental motto on the door of the TOGS barrette and, during the final dash to the Kuwait-Basra highway, Four One flew a lancers' flag from the radio antenna.

D: CHALLENGER I MK. 3 Command Tank, Brigade Headquarters, 7th Armoured Brigade, 1st (UK) Armoured Division, Southern Iraq, 26 February 1991 (Brig. Patrick Cordingley)

Effective command and control procedures are fundamental to the successful prosecution of manoeuvre warfare and the commanders of both 4th and 7th Armoured Brigades decided from the outset to direct their respective formations from an MBT during the land battle. 78KF91 is one of four command tanks built to the Mark 3 standard and it served as the mount of Brig. Patrick Cordingley, Commander 7th Armoured Brigade. Its callsign One Four Delta is carried on each hull side as is the black chevron mutual recognition



With the regimental insignia emblazoned on the TOGS door, a Challenger 1 Mk. 3 of 1st The Queen's Dragoon Guards thunders down a road in Central Bosnia during a routine patrol. (Media Ops Land Command)

device of the coalition forces. Along the right hand Chobham armour side plates are four brackets for water jerrycans; but only one is fitted to the other side of the tank on the rear bazooka plate. Tied to the rear central left hand Chobham armour plate is an engine air filter wrapped in CARM (Chemical Agent Resistant Material). Across the ERA (Explosive Reactive Armour) blocks on the lower glacis plate are sandbags which were intended to cover the tank's optical devices when in leaguer to prevent damage from artillery fragments, although they also served to prevent the driver, Cpl. Stavely, from barking his knees on the protruding bolts of the supplementary armour when climbing aboard the tank. On the front turret roof is the black chevron for identification to friendly aircraft with a yellow recognition panel at the rear of the turret. As a command tank, One Four Delta has three radio antennae, two of which carry pennants bearing the Desert Rats' jerrobo; the red one was sent to Brig. Cordingley as a Christmas gift from a former Desert Rat who came into possession of it following a parade by 7th Armoured Division to mark the Coronation in 1953. The pennant had been flown by successive generals commanding the division from 1942-1953. At that time 7th Armoured Division had 350 tanks which is almost exactly twice that of 1st (UK) Armoured Division in the Gulf of 176. On the side of the TOGS barrette is the castle motif of the 5th Royal Inniskilling Dragoon Guards with whom Brigadier Cordingley undertook his regimental service. To the rear on the TOGS compressor unit is another red jerrobo which is forever to be associated with the Desert Rats of 7th Armoured Brigade/ Division, hence One Four Delta and its commander were referred to by the troops as King Rat. The tank, however, was named *Bazoff's Revenge* in recognition of Farzad Bazoff, the journalist on *The Observer* newspaper who was executed by the Saddam Hussein regime for alleged spying. The name was thought up by the loader, L/Cpl. Colin Shaw who applied it to the fume extractor of the main armament with a black marker pen.



A Challenger I Mk. 2, 2nd Royal Tank Regiment, surges through a ford on the Drawsko Pomorski Training Area in Poland during Exercise Ulan Eagle in September 1996. With the denial of many training areas in Germany, Poland has become an important venue for battlegroup exercises in the British Army. (Media Production Centre Germany)

During the course of the land offensive, 7th Armoured Brigade destroyed 76 MBTs, 68 APCs, 18 artillery pieces and captured 3000 POWs. For his outstanding leadership throughout the campaign, Brig. Cordingley was awarded the Distinguished Service Order.

E1: CHALLENGER I MK. 3 Control Tank, D Squadron, Queen's Royal Irish Hussars Battle Group, 7th Armoured Brigade, 1st (UK) Armoured Division, Southern Iraq, 25 February 1991 (Maj. Toby Maddison)

DERRY was the first British tank to move out of the bridgehead created in the Iraqi frontlines by the 1st (US) Infantry Division (Mechanised) – 'The Big Red One'; crossing Phase Line New Jersey to lead the breakout of 7th Armoured Brigade at 1515 hours on 25 February 1991. The obligatory yellow air recognition panel is lashed down over the turret basket with the rectangular shaped TOGS indicator and Trimble GPS transponder stalk showing vertically from the turret roof. The callsign is repeated on the rear fuel drums with zero on the left and B on the right hand one, applied freehand in black paint. **1a** The scrap views show two examples of what was known as 'bin art' which became more prevalent as the date of the land offensive approached – a popular theme being characters from *VIZ* magazine, such as Biffa Bacon, whereas the classic pin-up is a direct response to the 'nose art' applied to Royal Air Force and USAF aircraft in the Gulf War. These two designs appeared on tanks of The Royal Scots Dragoon Guards. The vehicle registration number is 64KG97, visible only on the rear hull plate beside the right hand light cluster. **1b** All the tanks within QRIH were named after towns and villages in Ireland beginning with the squadron letter; the subject vehicle being

DERRY which caused a certain amount of contention among the interdenominational crew. The name is applied on each forward Chobham armour side plate with the crew zap code and the unit code 2/2/D below applied freehand in black paint. The unit code is also painted on the left front mud flap as viewed. Between the vehicle name and the zap code is the red jerboa of the Desert Rats. This also appears on the faces of the rear attachment points for the towing cables on the hull sides and above the right hand rear light cluster. **1c** With a richly embroidered pennant bearing the regimental insignia flying above the turret, Zero Bravo is the mount of the officer commanding D Squadron which was at the forefront of the QRIH Battle Group throughout much of the offensive; the squadron tally in the war being 22 T-55/59; one BMP-1; three MTLB; seven artillery pieces and six trucks. On the forward turret roof is the black chevron mutual recognition device which is repeated on the hull sides and on the rear of the turret basket; the latter being painted on the folded-out cardboard packaging of a 24-hour combat rations box. This and the two black side chevrons have metallic silver tape inserts which were intended to aid recognition through TOGS but they had no appreciable effect. Taped to the turret roof just in front of the commander's primary sight are detector papers which change colour when exposed to particular chemical or biological agents. A further black chevron is painted on the commander's hatch pointing forwards. Welded centrally to the nose of the tank is a metal bracket which acted as a step for the commander who had sustained a serious knee injury playing hockey; a device copied by several crews in the squadron. For his gallantry during the war, Maj. Toby Maddison, commanding D Squadron, was awarded the Military Cross.

E2: CHALLENGER ARMOURD REPAIR AND RECOVERY VEHICLE, 6th Forward Repair Group, Royal Electrical and Mechanical Engineers, 4th Armoured Brigade, 1st (UK) Armoured Division, Kuwait, 4 March 1991

With its ATLAS crane aloft, MOYRA, one of 12 CRARRVs deployed to the Gulf assists in the repair of vehicles soon

after the end of the war. The CRARRVs proved highly effective throughout the campaign and, during the actual conflict, were instrumental in towing several casualties to the finish line on the Basra road, on occasion pulling two AFVs at once. The first four CRARRVs, 70KG67-70, CHARITY; BIG GEORDIE; FAITH and HOPE respectively, were deployed in support of 7th Armoured Brigade. With the commitment of 4th Armoured Brigade and the creation of 1st (UK) Armoured Division, further CRAARVs were dispatched to the Gulf with MOYRA 70KG71; BIG ALMA 70KG72; CLARA 70KG73 and LABEL 70KG74 assigned to 4th Armoured Brigade and an additional two, FLORENCE (also known as FLOJO) 70KG75 and BERTHA 70KG76, to 7th Armoured Brigade. A further two, BARNBOW BELLE 70KG79 and BIG TYKE 70KG80, were held in the War Maintenance Reserve. Many of the names are redolent of the North East and Newcastle-upon-Tyne while the district in the city of Leeds where the vehicles were made gave rise to the name BARNBOW BELLE. Others were named after individuals; for instance, BIG ALMA was in recognition of the dynamic lady in the personnel department of Vickers Defence Systems.

F: CHALLENGER I MARK 2, 1st Armoured Squadron, The Queen's Royal Lancers, BATUS, Canada, June 1994 (Capt. Simon Vaughan-Edwards)

The British Army Training Unit Suffield (BATUS) comprises thousands of hectares of Canadian prairie where live firing of all calibres of weapons allows for the most realistic of field training exercises. In common with all British Army vehicles at Suffield, this Challenger is finished in sand yellow with green irregular stripes. The callsign Zero Charlie is painted with white stencils on black rectangles on each forward bazooka plate and turret side. The callsign is repeated on a metal plate attached to the rear of the turret basket. Forward of the callsign on each bazooka plate is the Zap Code 102, again painted in white on black. At BATUS, each vehicle has its own individual number or Zap Code. The vehicle registration number is 35KA89. The white painted fume extractor is an identifying feature of 1st Armoured Squadron, as is the white stripe down the edge of the rear bazooka plate which also acts as a reminder to the infantry that it is unsafe to be further forward of this line in case the tank fires its main armament. The red metal rectangular device at the commander's cupola indicates that the tank is 'at action'; a white circular one denotes that it is not 'at action' and has no live ammunition loaded in any of its weapons. The

callsign Zero Charlie indicates the second-in-command of the armoured squadron and he is further identified, as are troop leaders, by the single tennis ball impaled on the radio aerial; the squadron leader, Zero Bravo, has a radio aerial with two tennis balls - these balls being visible when dust kicked up by the tank obscures the painted callsigns. At the base of the aerial is a rear facing light cluster to aid station keeping at night. Attached to the rear of the turret basket is a metal tube with lights at each end that allows range safety staff to determine in which direction the turret is pointing at night. This tank also carries a fluorescent orange engineer minefield picket stake which is erected on the turret top when the tank is acting in the Intimate Support Troop role to the infantry. On the front of the turret is an inverted V painted in white which is known as the 'forty-fives'. The white V is visible through the commander's sight and is a marker to indicate safe arcs of fire as determined by range safety staff. Depicted during Exercise Gazala at the culmination of The Queen's Royal Lancers' deployment to BATUS in 1994, this Challenger is crewed by B Squadron. Being the mount of the

Showing the flag is an important aspect of peace keeping operations and this is demonstrated to fine effect by a Challenger 1 Mark 3 of Command Troop, Nunshigum Squadron, The Royal Scots Dragoon Guards (Carabiniers and Greys). (Media Ops Land Command)





squadron second-in-command, this is a Challenger Control Tank with a particular fit of VRC353 radios.

G1: CHALLENGER I MK. 3, B Squadron, The Queen's Royal Hussars, IFOR, Operation Resolute, Central Bosnia, 11 January 1996 (Sgt. Potter)

The Queen's Royal Hussars (The Queen's Own and Royal Irish) were formed from the amalgamation of The Queen's Own Hussars and the Queen's Royal Irish Hussars in September 1993. Following the peace agreement initiated in Dayton, Ohio, on 21 November 1995, the North Atlantic Council authorised the Supreme Allied Commander Europe to deploy Enabling Forces into Croatia and Bosnia-Herzegovina. On 5 December, NATO Foreign and Defence Ministers endorsed the deployment of a multi-national military Implementation Force (IFOR) drawn from all the NATO nations and with additional troops from 16 non-NATO countries. Britain's contribution to Operation Joint Endeavour included a detachment of The Queen's Royal Hussars comprising a small headquarters with two Challengers; two squadrons with 12 Challengers each; a Reconnaissance Troop with eight Scimitar CVR(T) and support elements including two reserve Challengers. The subject vehicle is depicted moving into the devastated area of Mrkonjić Grad on 11 January 1996. Flying a Union Flag emblazoned with a black pig, it bears the callsign Three One in yellow on a black background within a yellow stencilled rectangle on metal plates attached to the turret sides and rear, denoting D Squadron which has provided a complete troop to both A and B Squadrons. The stencilled callsign within a square on the forward bazooka plates shows

its attachment to B Squadron. Also on the bazooka plates are the black chevron mutual recognition device, redolent of the Gulf War, and the abbreviation IFOR painted in white on a black rectangle which has been wiped clean for higher visibility. **1a** On the door of the TOGS barbette is the regimental insignia of the QRH and on its top face is the black pig motif which is repeated on the lower hull front below the vehicle registration number 65KG35. Below that is the Military Load Classification of a black 70 within a solid grey circle. The black pig device was adopted as a squadron insignia by D Squadron, The Queen's Own Hussars on its formation in 1978 when the regiment was stationed in Detmold, West Germany. During festivities to mark the occasion, a certain Trooper Gould purloined a large black piggy bank from a local savings bank. The beast was then sawn in half and mounted behind the bar at Hobart Barracks. It adorned virtually every vehicle, item of clothing and artefact in the squadron thereafter. On the side of the TOGS barbette is the white fern leaf emblem of New Zealand marking the affiliation of the 3rd Hussars with 2nd New Zealand Division at the battle of El Alamein which was granted by General Lord Freyberg VC as commander of the New Zealand Expeditionary Force in World War 2. All the tanks in the QRH have names, beginning with the squadron letter, painted in black on the hullsides beside the driver's position. Although some tanks have inspirational names such as DESTINY, most recall regimental battle honours such as DETTINGEN, or place names in the regiment's recruiting areas of London, Birmingham, Northern Ireland and the West Midlands. This tank is named after the town of DROITWICH. On the rear mud flaps are high visibility yellow and orange



INDEX

(References to illustrations are shown in **bold**. Plates are shown with caption locators in brackets.)

- 1st British Corps 36
1st (UK) Armoured Division 54, 38–39, 39, 40, C (43), D (43–44), E (44–45), G2 (47)
2nd Royal Tank Regiment 15, 16, 17, 20, 35, 44, G2 (47)
4th Armoured Brigade 38, 38–39, B (42), 45
7th Armoured Brigade 36, 36–37, 37–38, A2 (41), C (43), D (43–44), E1 (44), 45, G2 (47)
14th/20th King's Hussars 39, 40, 42, B (42)
17th/21st Lancers 16, 17, 43
- air recognition panels D (43)
ammunition 4, 6, 8, 12, 22, 23, 33
 depleted uranium 39
 HEAT 4–5, 13
 HESH 4–5
Anglo-German collaboration 5, 6, 6–7, 23, 34
anti-tank weapons 5–4, 5–6, 13
Arab-Israeli War, 1967: 3
 armament, main 4, 6, 8, 12, 20, 23, 23–24, 35
 ammour 4–5, 9, 13, 22, 37, 39
 armoured bus 39
 availability 41
- Bosnia 42, 43, G1 (46–47)
bridging classification A1b (41)
British Army Training Unit Suffield (BATUS) 45
- camouflage schemes A1 (41), F (45), G2 (47)
Canadian Army Trophy, the 16–23, 21 (table), 37
 enquiry 24, 33
Centurion MBT and variants 3, 6, 36, 38
Challenger 2: 24, 33, 33, 34, 35, 35
Chiefain/Challenger Armament programme
 (CHARM) 23–24
Chiefain/Challenger Improvement Programme
 (CHIP) 23–24
Chiefain MBT 3, 3, 4, 4, 6, 7, 16–17, 23, 24, 36
Chiefain Replacement Programme 33–34
command tanks B (42), D (43–44), G2 (47)
commander, the 11, 12, 13
comparative trials 33–34
Computerised Sighting System (CSS), the 12–13
confidence in 40
contractors 35, 37
Control Tanks 15, E1 (44), F (45–46)
cupola, the 12
- defence cuts 35, 47
delivery 10
design and development 3, 3, 5, 6–7, 8–10, 24, 35
disposal 35
drivers compartment 11–12
- engines 7, 9, 14
- Federal Republic of Germany 5, 6
fighting compartment 11, 11
fire control system 11, 16, 16–17
fuel tanks 15, 39
Future Main Battle Tank 5, 6, 6–7
Future Main Battle Tank 2000: 23
 FV4030 4, 7–8, 9, 9
 FV4211 5, 5
- Global Positioning System (GPS) 40, B (42)
Gulf War, the 13, 14, 34–35, 36, 36–40, 37, 39, 40, A2 (41), B (42), C (43), D (43–44), E (44–45)
gunner, the 11, 12–13
gunnery 19–20, 21 (table), 21–22
Gunnery Sighting System (GSS), the 13
- Imperial Iranian Army 3, 4, 7–8
Improved Computerised Sighting System (ICSS) 17, 22, 33
internal layout D, 11
Iraqi forces 34, 36, 39, 40
Israeli forces 6
- Jagdchieftain, the 6
- Leopard 1 MBT 6
Leopard 2 MBT 6, 8, 22, 33, 34, 41
Life Guards, the 39
- M-1 Abrams MBT 5, 13, 22, 33, 34
markings 40, A1 (41), B (42), C (43), E1a (44)
 calligns 23, A (41), D (43), F (45), G (46–47)
 zap codes Ca (43), F (45)
- MBT-80: 7, 8–9
Mid-Life Improvement Programme 35
mobility 13
modifications 9, 18, 23–24
 Gulf War 37, 37, 37–38, 39, 39
Muzzle Reference System, the 13
- NATO, standardisation within 5, 8, 34
- orders 9, 16, 35
organisation 35, 36, 47
- periscopes 12
powerpack, the 13–14
problems 9–10
- Queen's Dragoon Guards 43
Queen's Royal Hussars 42, G1 (46–47)
- Queen's Royal Irish Hussars 16, 17, 24, 37, 39, C (43), E1 (44), 46
Queen's Royal Lancers F (45–46)
- rangefinders 12, 34
regimental insignia A1a (41), 43, Cb (43), G1a (46), G2b (47)
Royal Armoured Corps 35, 36
 CAT enquiry 24, 35
Royal Hussars, the 10, 10, 12, 14, 16, 18, A1 (41) and the Canadian Army Trophy 1987: 18–21
Royal Jordanian Army 8
Royal Regiment of Fusiliers 39
Royal Scots Dragoon Guards 16–17, 22, 35, 36, 36, 37, 38, 39, 39, 40, A2 (41), 45, 47
- scale drawings 16, 19, 38, 46
sights 12, 22, 34
smoke generating system 37, 38
Soviet forces 4, 9, 13, 39
specifications D
speed 10, 22
Staffordshire Regiment 37
steering units 9
survivability 13
suspension 9, 14
Symbology Processing Unit (SPU), the 13
- tank fleet strength 23, 36
Thatcher, Margaret, Baroness (1925–) 41
Thermal Exhaust Cowl 33
Thermal Imager Sensor Head (TISH), the 15, 15, 21
Thermal Observation and Gunnery System (TOGS), the 10, 11, 13, 18, 21, 21, 54, 39, 39
Thermal Observation and Gunnery System indicators 40, A2a (41), C (43)
Thermal Surveillance System (TSS), the 13
transmission 9, 14
trials 9–10, 33–34, 34
turret, the 6, 11, 15, 23, 33
- variants 15–16
 armoured repair and recovery 14–15, 16, 17, 18, 37, 38, 42, E2 (44–45), 47
 training tank 15, 19, 35
Vickers Defences Systems 14, 15, 24
- Warsaw Pact, collapse of 34, 47
- XM-1 5, 8
- Yom Kippur War, 1973: 5–6

Related titles & companion series from Osprey

ELITE (ELI)

Uniforms, equipment, tactics and personalities of troops and commanders

- 0850455731 ELI 001 THE PARAS 1940-84
085045574X ELI 002 THE US MARINE CORPS SINCE 1945
085045610X ELI 004 US ARMY SPECIAL FORCES 1952-84
0850457300 ELI 010 WARSAW PACT GROUND FORCES
0850457955 ELI 013 US ARMY RANGERS & LRRP UNITS 1942-87
0850458226 ELI 016 NATO ARMIES TODAY
0850458374 ELI 018 ISRAELI ELITE UNITS SINCE 1948
085045865X ELI 022 WORLD SPECIAL FORCES INSIGNIA
0850459419 ELI 029 VIETNAM AIRBORNE
185532251X ELI 043 VIETNAM MARINES 1965-73
1855322773 ELI 045 ARMIES OF THE GULF WAR
1855322943 ELI 047 SOUTH AFRICAN SPECIAL FORCES
1855323575 ELI 049 THE GURKHAS
1855323672 ELI 053 INTERNATIONAL BRIGADES IN SPAIN 1936-39
1855323915 ELI 055 MARINE RECON 1940-90
1841761419 ELI 068 THE MILITARY SNIPER SINCE 1914
1841761966 ELI 075 THE INDIAN ARMY 1914-47
1841761842 ELI 076 THE GERMAN FREIKORPS 1918-23

ESSENTIAL HISTORIES (ESS)

Concise overviews of major wars and theatres of war

- 1841762822 ESS 008 THE KOREAN WAR
1841764221 ESS 015 THE FALKLANDS WAR 1982
1841763713 ESS 020 IRAN-IRAQ WAR 1980-1988
1841764191 ESS 038 THE VIETNAM WAR 1956-1975
1841765740 ESS 055 THE GULF WAR 1991

NEW VANGUARD (NVG)

Design, development and operation of the machinery of war

- 1855322838 NVG 002 M1 ABRAMS MAIN BATTLE TANK 1982-92
1855323389 NVG 006 T-72 MAIN BATTLE TANK 1974-93
1855323796 NVG 010 WARRIOR MECHANISED COMBAT VEHICLE 1987-94
1855324334 NVG 012 BMP INFANTRY FIGHTING VEHICLE 1967-94
1855325381 NVG 018 M2/M3 BRADLEY INFANTRY FIGHTING VEHICLE 1983-95
1855326434 NVG 021 MERKAVA MAIN BATTLE TANK MKS I & II
1855324857 NVG 023 CHALLENGER MAIN BATTLE TANK 1982-97
1855328259 NVG 031 THE M47 AND M48 PATTON TANKS
1841762024 NVG 035 M26/M46 PERSHING TANK 1945-53
1841764159 NVG 052 CADILLAC GAGE V-100 COMMANDO 1960-71
184176387X NVG 068 CENTURION UNIVERSAL TANK 1943-2003
1841765422 NVG 073 M4 (76MM) SHERMAN MEDIUM TANK 1943-65
1841765406 NVG 077 M24 CHAFFEE LIGHT TANK 1943-85

WARRIOR (WAR)

Motivation, training, combat experiences and equipment of individual soldiers

- 185532542X WAR 023 US MARINE IN VIETNAM 1965-73
1855325683 WAR 028 GREEN BERET IN VIETNAM 1957-73

CAMPAIGN (CAM)

Strategies, tactics and battle experiences of opposing armies

- 0850459605 CAM 004 TET OFFENSIVE 1968
1855327384 CAM 060 THE EBRO 1938
1841762202 CAM 118 THE YOM KIPPUR WAR 1973 (1)
1841762210 CAM 126 THE YOM KIPPUR WAR 1973 (2)

MEN-AT-ARMS (MAA)

Uniforms, equipment, history and organisation of troops

- 0850453607 MAA 104 ARMIES OF THE VIETNAM WAR 1962-75
1855328399 MAA 108 BRITISH INFANTRY EQUIPMENTS (2) 1908-2000
0850453968 MAA 116 THE SPECIAL AIR SERVICE
0850454182 MAA 123 THE AUSTRALIAN ARMY AT WAR 1899-1975
0850454506 MAA 127 THE ISRAELI ARMY IN THE MIDDLE EAST WARS 1948-73
0850454824 MAA 133 BATTLE FOR THE FALKLANDS (1) LAND FORCES
0850454921 MAA 134 BATTLE FOR THE FALKLANDS (2) NAVAL FORCES
085045493X MAA 135 BATTLE FOR THE FALKLANDS (3) AIR FORCES
0850455146 MAA 143 ARMIES OF THE VIETNAM WAR (2)
0850456002 MAA 164 THE CANADIAN ARMY AT WAR
0850456851 MAA 174 THE KOREAN WAR 1950-53
0850458420 MAA 205 US ARMY COMBAT EQUIPMENTS 1910-88
1855326086 MAA 293 THE RUSSIAN CIVIL WAR (1) THE RED ARMY
1855326213 MAA 300 FRENCH FOREIGN LEGION SINCE 1945
1855326566 MAA 305 THE RUSSIAN CIVIL WAR (2) WHITE ARMIES
1855326655 MAA 306 CHINESE CIVIL WAR ARMIES 1911-49
1855326922 MAA 309 THE ITALIAN INVASION OF ABYSSINIA 1935-36
1855326582 MAA 312 THE ALGERIAN WAR 1954-62
1855327899 MAA 322 THE FRENCH INDOCHINA WAR 1946-54

FORTRESS (FOR)

Design, technology and history of key fortresses, strategic positions and defensive systems

Contact us for more details – see below

AIRCRAFT OF THE ACES (ACE)

Experiences and achievements of 'ace' fighter pilots

- 1855325012 ACE 004 KOREAN WAR ACES

AVIATION ELITE UNITS (AEU)

Combat histories of fighter or bomber units

Contact us for more details – see below

COMBAT AIRCRAFT (COM)

History, technology and crews of military aircraft

Contact us for more details – see below

To order any of these titles, or for more information on Osprey Publishing, contact:

Osprey Direct (UK) Tel: +44 (0)1933 443863 Fax: +44 (0)1933 443849 E-mail: info@ospreydirect.co.uk

Osprey Direct (USA) c/o MBI Publishing Toll-free: 1 800 826 6600 Phone: 1 715 294 3345


Fax: 1 715 294 4448 E-mail: info@ospreydirectusa.com

www.ospreypublishing.com

The design, development, operation and history of the machinery of warfare through the ages.



Full colour artwork



Cutaway artwork



Unrivalled detail



Photographs

Challenger Main Battle Tank 1982–97

Work began in 1976 on development of the Challenger, a new MBT specifically for the Iranian army who needed a more capable tank than the Chieftain to suit their climatic and geographical conditions. However, when the Iranian revolution occurred in 1979 the British army was reluctantly forced to accept this new design themselves. Once in service, technical problems led to various modifications, but the Challenger went on to great success in the Gulf War, playing crucial roles in both Operations Desert Storm and Desert Sabre. In this book Simon Dunstan examines this tank in detail, evaluating its performance both on the test range and in the field of battle.

OSPREY
PUBLISHING

www.ospreypublishing.com

ISBN 1-85532-485-7



9 781855 324855